

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



Characteristics

- Heavy-duty industrial wet/dry Sump Cleaning & Fluid Recycling System can clean virtually any machine tool sump, tank, or pit
- Thoroughly removes the coolant, sludge, and chips from the sump
- Filters the sludge and separates the chips from the coolant
- Quickly returns the filtered coolant to the sump; or transports the coolant to waste treatment for disposal or to a recycling system
- 120-volt, single phase, 3-stage motor assembly generates 10" HG vacuum
- Suction rates up to 85 GPM while being able to pick up chips, sludge, grinding swarf, etc
- Discharge pressure of 5 PSI for discharge rates of up to 40 GPM on water-based fluids
- Electric high level float switch to shut motor off when unit is full
- Push around configuration. Compact design with small footprint
- Equipped with two 4" x 2" swivel casters and two rigid casters
- Dimensions: 44" long x 23.5" wide x 51" high
- Fluid recovery capacity: 50 gallons (190 Liters)
- Rectangular chip basket with poly filter sleeve. Recovery capacity: 1.6 cubic foot (.45 cubic meter)
- Complete with hoses and cleaning tools: - 2" 10' oil resistant suction hose - 1-1/2" x 10' discharge hose - 2" x 3' aluminum cleaning tool

Specifications

50 GALLON ELECTRIC SUMP CLEANER & FLUID RECYCLING SYSTEM	112606
Model Name	50 GALLON SUMP CLEANER & FLUID RECYCLING SYSTEM
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	1550 W
Power	2 HP
Amperage	14 A
Air Flow	102.5 CFM
Vacuum Pressure	146 " H ₂ O
Sound Level	76 dB(A)
Type of Power Outlet	20 Amps
Suction Inlet Port	2 "
Cart Type	Carriage Base (CB)
Recovery Capacity (Tank)	50 gal.
Rectangular Chip Basket Capacity	12 gal.
Length	44 "
Width	23.5 "
Height	51 "
Weight (Vacuum Only)	350 lb.
Cord Length	22 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Rectangular Chip Basket with Poly Filter Sleeve - Included



2" Oil Resistant Suction Hose and Wand - Included



1-1/2" Oil Resistant Discharge Hose with Gasoline Type Discharge Handle - Included



50 Gallon Sump - System Overview