

### U.S. Headquarters

**Tiger-Vac Inc.**  
11 SW 12th Ave #112  
Dania, FL 33004  
USA

Tel: 1-800-668-4437 (954-925-3625)  
Fax: 1-800-668-4439 (954-925-3626)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



CLEANING MACHINES FOR  
UNCLASSIFIED (GENERAL PURPOSE)  
AREAS  
All the electrical components are certified by  
an NRTL such as UL, CSA or ETL



Chip and  
Coolant  
Recovery

## Specifications For GS1/78L OIL

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet
GS1/78L OIL	111894A	120 V	60 Hz	Single	1200 W	1.5 HP	10 A	111 CFM	120 " H <sub>2</sub> O	15 Amps
	Dimensions: H39" x W24" x L22"      Weight: 58 lb.      Sound Level: 72 dB(A)									

Please note that specifications are subject to change without notice

## Technical Sheet For GS1/78L OIL

### FILTERS - Included

Part #	Description
220078	POLYESTER FILTER CARTRIDGE FOR MODEL GS 78L OIL
220080	FLOAT ASSEMBLY FOR MODEL GS 78L OIL

### CONNECTOR FOR SUCTION HOSE - Included

Part #	Description
500722	METAL CONNECTOR 60/50mm (MACHINE SIDE), FOR USE WITH 60mm METAL INLET FOR PLANET SERIES

### TOOLS AND ACCESSORIES - Optional

Part #	Description
500387	CLEAR (PU) POLYURETHANE SUCTION HOSE ASSEMBLY 2"(50mm) X 10' (3m) w/HOSE CUFFS ON BOTH ENDS
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR
500790	DOUBLE BEND WAND ASSEMBLY 2" (50mm), CHROME PLATED STEEL, WITH TOOL COUPLING INSTALLED
500794	OIL RESISTANT FLOOR TOOL 2"(50mm) x 12"(300mm), w/PLASTIC WHEELS, w/POLYPROPYLENE BRISTLES