

## Characteristics



Wet and  
Dry  
Recovery



- Designed for the recovery of chips mixed with coolant
- Pneumatic (air-operated)
- Can run continuously without overheating or wear
- Sieve basket separates chips from coolant. Chips stay in the basket and coolant is recovered in the recovery tank
- Liquid recovery capacity of 6.08 gal. (23L) of coolant in the recovery tank, and 7.13 gal. (27L) of chips in the sieve basket
- Filtration system consists of a main filter and mist arrestor pack
- High density polyethylene recovery tank is corrosion resistant and oil resistant
- Mounted on a Tilting Cart (TC) for easy disposal of recovered materials
- Silent operation
- Liquid level indicator included
- Drain hose assembly included

## Specifications

HOGOIL-57L (TC) AIR	112350	112351
<b>Model Name</b>	HOGOIL-57L (TC) AIR	HOGOIL-57L (TC) AIR
<b>Type (Powerhead)</b>	Pneumatic	Pneumatic
<b>Venturi</b>	Single	Single
<b>Venturi (diam.)</b>	6 mm	6 mm
<b>Minimum Compressor</b>	15 HP	15 HP
<b>Air Line Size (Diam.)</b>	1/2 "	1/2 "
<b>Input Air Volume</b>	45 CFM	45 CFM
<b>Input Air Pressure</b>	80 PSI	80 PSI
<b>Air Flow</b>	125 CFM	125 CFM
<b>Vacuum Pressure</b>	190 " H <sub>2</sub> O	190 " H <sub>2</sub> O
<b>Suction Inlet Port</b>	2 "	2 "
<b>Cart Type</b>	Tilt Cart (TC)	Tilt Cart (TC)
<b>Filter Cleaning</b>	None	None
<b>Recovery Capacity - Sieve Basket</b>	7.13 gal.	7.13 gal.
<b>Liquid Recovery Capacity</b>	6.08 gal.	6.08 gal.

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



HOGOIL Drain Hose Assembly - Included



HOGOIL-57L Powder Coated Sieve Basket - Included



Optional Forklift Lifting Rails available



HOGOIL-57L (TC) AIR with Stainless Steel Tank