

### U.S. Headquarters

**Tiger-Vac Inc.**  
11 SW 12th Ave #112  
Dania, FL 33004  
USA

Tel: 1-800-668-4437 (954-925-3625)  
Fax: 1-800-668-4439 (954-925-3626)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



CLEANING MACHINES FOR  
UNCLASSIFIED (GENERAL PURPOSE)  
AREAS  
All the electrical components are certified by  
an NRTL such as UL, CSA or ETL



Chip and  
Coolant  
Recovery



Internal Pump

## Specifications For HOGOIL PUMP

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
<b>HOGOIL PUMP</b>	<b>112652A</b>	120 V	60 Hz	Single	2040 W	2.7 HP	15.2 A	200 CFM	90 " H <sub>2</sub> O	20 Amps	8 Gal
		Dimensions: H49" x W22.5" x L26"		Weight: 127 lb.		Sound Level: 75 dB(A)					

Please note that specifications are subject to change without notice

## Technical Sheet For HOGOIL PUMP

### FILTERS - Included

Part #	Description
219906	POLYPROPYLENE MESH FILTER w/CLAMP, FOR SIEVE BASKET FOR HOGOIL PUMP (WIRE CAGE SOLD SEPARATELY)
219907	DRALON FILTER ASSEMBLY WITH CLAMP, FOR HOGOIL PUMP AND HOGOIL STANDARD
219908	FOAM FILTER (SET OF 2pcs) FOR HOGOIL PUMP AND HOGOIL STANDARD
216900	LIQUID FILTER ASSEMBLY FOR PUMP INTAKE FOR MEC620 LIQUID PUMP OUT

### CONNECTOR FOR SUCTION HOSE - Included

Part #	Description
500780	CONNECTOR, w/LOCK PIN, FOR SUCTION HOSE, FOR HOGOIL PUMP AND HOGOIL STANDARD

### TOOLS AND ACCESSORIES - Optional

Part #	Description
500387	CLEAR (PU) POLYURETHANE SUCTION HOSE ASSEMBLY 2"(50mm) X 10' (3m) w/HOSE CUFFS ON BOTH ENDS
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR
500790	DOUBLE BEND WAND ASSEMBLY 2" (50mm), CHROME PLATED STEEL, WITH TOOL COUPLING INSTALLED
500794	OIL RESISTANT FLOOR TOOL 2"(50mm) x 12"(300mm), w/PLASTIC WHEELS, w/POLYPROPYLENE BRISTLES