



EXP1 Models Certified for:

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)  
Class I, Division 1, Division 2, Group D, T3C and Class II, Division 1, Division 2, Groups E, F and G



**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts and Flammable Liquids

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.  
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)




Complies with NFPA 77 "Recommended Practice on Static Electricity"

## Characteristics



EX Certified



Less than 10 ohms



Activated Carbon



Wet Recovery



SS 304



- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- Available with an optional activated carbon cartridge for the adsorption of toxic/noxious fumes and vapors
- Designed for aircraft de-fueling and de-puddling
- Single phase explosion proof/dust ignition proof motor
- For wet & dry recovery
- All stainless steel Type 304 construction (except cart)
- With red & yellow bands
- Equipped with a heavy duty powder coated tilting cart and stainless steel drain valve for easy emptying of recovered materials
- Stainless steel cart available

## Specifications

EXP1-15 to 55 (TC) TE SERIES	110253A	110256A	110261A
<b>Model Name</b>	EXP1-15 (TC) TE	EXP1-25 (TC) TE	EXP1-55 (TC) TE
<b>Type (Powerhead)</b>	Electric	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes	Yes
<b>Tension</b>	120 V	120 V	120 V
<b>Frequency</b>	60 Hz	60 Hz	60 Hz
<b>Phase</b>	Single	Single	Single
<b>Wattage</b>	1000 W	1000 W	1000 W
<b>Power</b>	1.3 HP	1.3 HP	1.3 HP
<b>Amperage</b>	9 A	9 A	9 A
<b>Air Flow</b>	132 CFM	132 CFM	132 CFM
<b>Vacuum Pressure</b>	69 " H <sub>2</sub> O	69 " H <sub>2</sub> O	69 " H <sub>2</sub> O
<b>Sound Level</b>	78/85 dB(A)	78/85 dB(A)	78/85 dB(A)
<b>Type of Power Outlet</b>	Not Included	Not Included	Not Included
<b>Suction Inlet Port</b>	1.5 "	1.5 "	2 "
<b>Cart Type</b>	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)
<b>Filter Cleaning</b>	None	None	None
<b>Dust Recovery Tank</b>	10 gal.	15 Gal	40 Gal
<b>Liquid Recovery Capacity</b>	12.5 gal.	17 gal.	45 gal.
<b>Length</b>	30 "	30 "	40 "
<b>Width</b>	27 "	27 "	30 "
<b>Height</b>	39 "	43 "	50 "
<b>Weight (Vacuum Only)</b>	102 lb.	104 lb.	150 lb.
<b>Cord Length</b>	50 ft.	50 ft.	50 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



Activated Carbon Cartridge for TE Series - Optional




Nitrile Suction Hose - Included



EXP1-25 (TC) TE



EXP1-55 (TC) TE



Strainer Basket for TE Series - Included



Grounding reel with stainless steel housing and cable - Optional