

U.S. Headquarters

Tiger-Vac Inc.
11 SW 12th Ave #112
Dania, FL 33004
USA

Tel: 1-800-668-4437 (954-925-3625)
Fax: 1-800-668-4439 (954-925-3626)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



DUST IGNITION PROTECTED

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)

Division 2, Class II, Groups F & G
Certified Zone 22 Hazardous Areas / Dust Group IIIC (Conductive Dusts)



IECEx 3rd Party Certified
Ex h tc IIIC T200°C (T85°C for BLSD version) Dc IP6X
IECEx LCIE 15.0048



This model can be used to Recover Combustible/Conductive Dusts in Hazardous Locations Division 2 and Zone 22 Dust Group IIIC:

Group F Conductive Carbonaceous Dust (carbon black, coal, coke dust, etc)
Group G All flour Dust (grain, flour, starch, sugar, wood, plastic, chemical dust, etc)
Group IIIC Conductive Dust Zone 22 (as per International Standards)

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Complies with NFPA 77 "Recommended Practice on Static Electricity"



Static Dissipating



HEPA - Included



High Filtration Efficiency Unit



Stainless General



SD Accessories - Included



Dry Recovery



Detachable Tank



EX Certified



3D Printing



Brushless Motor Available

Specifications For C-10 EX DT (MFS)

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
C-10 EX DT (MFS)	111786A	120 V	60 Hz	Single	1207 W	1.6 HP	10.5 A	110 CFM	107 " H ₂ O	120V	6.6 Gal
	Dimensions: H44" x W26" x L26" Weight: 87 lb. Sound Level: 72 dB(A)										
	Description: Equipped with a Universal Motor. Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										

Please note that specifications are subject to change without notice

Technical Sheet For C-10 EX DT (MFS)

HEPA FILTERS - Included	
Part #	Description
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION
215372	HEPA FILTER WITH GASKETS ON BOTH SIDES, 99.99% ON 0.3 MICRON, 11.522" OD x 9.066" ID x 2" HIGH
211854	HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH

FILTERS AND ACCESSORIES - Included	
Part #	Description
215177A	MAIN FILTER ASSEMBLY SD* PTFE, w/GASKET & RING, w/LACES, FOR SS/EXP-20 DT (CAGE SOLD SEPARATELY)
214880B	WIRE CAGE FOR FILTER -POWDER COATED

PRE-FILTER - Optional	
Part #	Description
215179	PREFILTER ONLY WITH ELASTIC, SD*

POLY LINER RECOVERY BAGS AND ACCESSORIES - Included	
Part #	Description
212100DS	CONDUCTIVE POLY LINER WITH DRAW STRING (20/25 LITRES)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

TOOLS AND ACCESSORIES - Included	
Part #	Description
383440D	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY 1.5"(38mm) x 10'(3m)FOR USE w/60mm CONDUCTIVE INLET
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM