2D-10 (IT-40L) DT CFE HEPA ORDLOC-652 W/3D Mini Enhanced Immersion Separator - Wet Mix (Water or Oil)


The name to vacuum with



NFPA 77

Applicable Requirements : ANSI/UL 1017 CSA C22.2 No.243

Complies with NFPA 77 "Recommended Practice on Static Electricity'



TOOL KIT



- Protected against ingress of dust
- Enhanced Mini Immersion Separator Wet Mix Can be used with either water or oil
- Designed for the recovery and INERTIZATION of combustible dust into a liquid immersion bath
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Electric
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- Recovery tank made of stainless steel Type 304
- A package of the disposable conductive "wet" recovery bags is included with the vacuum cleaner
- Recovery capacity 3.25 gal. (12.3L) of liquid is required in the recovery tank. The conductive "wet" Recovery Bag has a recovery capacity of 4.5L (1.5 gal.)
- Degassing vent allows gas to be evacuated automatically from the unit
- Equipped with a liquid level indicator
- Includes a complete static dissipative tool kit



Tiger-Vac Inc. 11 SW 12th Ave #112 Dania. FL 33004 USA

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval. Quebec Canada H7L 5W2

Website: http://www.tiger-vac.com Email: sales@tiger-vac.com

## **Specifications**

| 2D-10 (IT-40L) DT CFE HEPA ORDLOC-652 W/3D TOOL<br>KIT | 113189A-3D                               |
|--|--|
| Model Name   | 2D-10 (IT-40L) DT CFE HEPA W/3D TOOL KIT |
| Type (Powerhead)                                       | Electric                                 |
| Tension  | 120 V                                    |
| Frequency  | 60 Hz                                    |
| Phase  | Single                                   |
| Wattage  | 1207 W                                   |
| Power  | 1.6 HP                                   |
| Amperage   | 10.5 A                                   |
| Air Flow   | 110 CFM                                  |
| Vacuum Pressure  | 107 " H <sub>2</sub> 0                   |
| Sound Level  | 75 dB(A)                                 |
| Type of Power Outlet                                   | 120V                                     |
| Suction Inlet Port                                     | 1.5 "                                    |
| Cart Type  | Detachable Tank (DT)                     |
| Filter Cleaning  | Liquid Immersion Bath                    |
| Cord Length  | 35 ft.                                   |

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



**Optional 3D Tools** 



Mini Enhanced - Side View with detachable tank



Coalescing HEPA filter (Upstream) - Included





Mini Enhanced - Rear View



Mist Arrester Pack - Included



Conductive "wet" recovery bag - Included

**Tiger-Vac Inc.** 11 SW 12th Ave #112 Dania, FL 33004 USA **Tiger-Vac International Inc.** 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2 2D 10.(1 Tel: 1-800-668-4437 (954-925-3625) Fax: 1-800-668-4439 (954-925-3626)

Website: http://www.tiger-vac.com Email: sales@tiger-vac.com

L 5W2 2D-10 (IT-40L) DT CFE HEPA ORDLOC-652 W/3D TOOL KIT Brochure - Downloaded: July 8, 2024 - Page 2/3



Cone assembly and detachable recovery tank with liquid level indicator and drain valve - Included 3D To



Longer Life Brushless Motor Available (always with 2 x H14 HEPA filters)



**Degassing Vent - Included** 



3D Tool Kit for 1.5" camlock suction inlet - included



#228093 - Depressor cage for conductive wet recovery bag - optional