



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243

### Characteristics



Coalescing  
Filter Element




SD Accessories  
- Included



Dry Recovery




Stainless  
General



HEPA -  
Included



High Filtration  
Efficiency Unit



Wet Mix - Water



3D Printing



- Protected against ingress of dust
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Recovery capacity of 11 lb (5 kg) of dust into 6.5 gal. (25L) of water (no oil)
- Brushless motor available

## Specifications

2D-15 (IT-63L) CFE HEPA W/3D TOOL KIT	113187A-3D
<b>Model Name</b>	2D-15 (IT-63L) CFE HEPA W/3D TOOL KIT
<b>Type (Powerhead)</b>	Electric
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	1207 W
<b>Power</b>	1.6 HP
<b>Amperage</b>	10.5 A
<b>Air Flow</b>	110 CFM
<b>Vacuum Pressure</b>	107 " H <sub>2</sub> O
<b>Sound Level</b>	75 dB(A)
<b>Type of Power Outlet</b>	120V
<b>Suction Inlet Port</b>	2 "
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	Liquid Immersion Bath
<b>Length</b>	31 "
<b>Width</b>	24 "
<b>Height</b>	63 "
<b>Weight (Vacuum Only)</b>	180 lb.
<b>Cord Length</b>	35 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



2D-15 (IT-63L) with Recovery Tank removed



Mist Arrestor Pack - Optional



Coalescing HEPA filter (Upstream) - Included



Liquid Level Indicator Tube - Included



Sieve Basket - Included



Cone for Interceptors - Included



3D Tool Kit for 2" camlock suction inlet - included



Optional 3D Tools



Degassing Vent - Included