

...The name to vacuum with



CD-EX Models Certified for:

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)

Division 1, Class I, Group D and Class II, Groups E, F and G, T3C
Division 2, Class I, Group D and Class II, Groups F and G, T3C



CD EX Series **IECEX** 3rd Party Certified

Ex d IIB T4 Gb
Ex t IIIC T135°C Db IP65
IECEX LCI 10.0040 X

Certified for providing an Equipment Protection Level of EPL Db and EPL Gb



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Complies with NFPA 77 "Recommended Practice on Static Electricity"

Characteristics




Continuous Duty



EX Certified



Dry Recovery




Wet Mix - Oil



HEPA - Included



High Filtration Efficiency Unit



Less than 10 ohms



SS 304



Coalescing Filter Element



- Hydrogen safe
- Immersion separator "Wet Oil Mix" - Meant to be used with mineral oil or any other neutralizing liquid
- **Designed for the Recovery and INERTIZATION of Conductive and Explosive Dust, such as Aluminum, Magnesium, Zirconium and other commercial alloys, into a Liquid Immersion Bath**
- Group E motor (metal dust) and switch included
- Legally certified explosion proof/dust ignition proof
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Less than 10 ohms of resistivity
- Coalescing Filter Element (CFE) for moisture removal
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Continuous duty single phase or 3-phase (TEFC) explosion proof/dust ignition proof motor
- stainless steel Type 304 interceptor tank
- Recovery capacity of 22 lb (10 kg) of dust into 7.9 gal. (30L) of oil or any other neutralizing liquid
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a liquid level indicator
- Other motor performances available

Specifications

CD-IT (85L) EX (CFE) SK HEPA	113129A3	113130A1	113130A2	113130A4	113130A5
Model Name	CD-IT (85L) EX (CFE) SK HEPA	CD-IT (85L) EX (CFE) SK HEPA	CD-IT (85L) EX (CFE) SK HEPA	CD-IT (85L) EX (CFE) SK HEPA	CD-IT (85L) EX (CFE) SK HEPA
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes
Tension	120 V	460 V	230 V	230 V	575 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Single	Three	Three	Single	Three
Wattage	1110 W	1480 W	1480 W	1480 W	1480 W
Power	1.5 HP	2 HP	2 HP	2 HP	2 HP
Amperage	15 A	2.6 A	5.2 A	12 A	2.1 A
Air Flow	125 CFM	158 CFM	158 CFM	158 CFM	158 CFM
Vacuum Pressure	120 " H ₂ O	130 " H ₂ O	130 " H ₂ O	130 " H ₂ O	130 " H ₂ O
VRV Setting	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O
Sound Level	74 dB(A)	74 dB(A)	74 dB(A)	74 dB(A)	74 dB(A)
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet Port	2 "	2 "	2 "	2 "	2 "
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	None	None	None	None	None
Length	47 "	47 "	47 "	47 "	47 "
Width	32 "	32 "	32 "	32 "	32 "
Height	62 "	62 "	62 "	62 "	62 "
Weight (Vacuum Only)	245 lb.	245 lb.	245 lb.	245 lb.	245 lb.
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



CD-IT (85L) with Recovery Tank removed



Coalescing Filter Element (CFE) - Included



HEPA Filter - Included



Liquid Level Indicator Tube - Included



Sieve Basket - Included




Cone for Interceptors - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included



Wye Connector - Included



Rupture Disk - Optional