



EXP1 Models Certified for:

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)  
Class I, Division 1, Division 2, Group D, T3C and Class II, Division 1, Division 2, Groups E, F and G



**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)




Complies with NFPA 77 "Recommended Practice on Static Electricity"

### Characteristics




EX Certified



Less than 10 ohms



Dry Recovery



Wet Mix - Water



HEPA - Included



High Filtration Efficiency Unit



SS 304



Detachable Tank



Coalescing Filter Element



- Immersion separator "Wet (Water) Mix" - Only meant to be used with water (no oil)
- **Designed for the Recovery and INERTIZATION of Conductive and Explosive Dust, such as Aluminum, Magnesium, Zirconium and other commercial alloys, into a Liquid Immersion Bath**
- Legally certified explosion proof/dust ignition proof
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Less than 10 ohms of resistivity
- Coalescing Filter Element (CFE) for moisture removal
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Electric
- Stainless steel Type 304 interceptor tank
- Recovery capacity of 11 lb (5 kg) of dust into 6.5 gal. (25L) of water (no oil)
- Degassing vent allows gas to be evacuated automatically from the unit
- Portable and equipped with a single, or dual, static dissipative suction hose connector
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a liquid level indicator
- Tiger-Vac® carries a large inventory of shrouded sanders, grinders and dustless drill kits, along with a large suction port for maximum dust recovery
- OSHA Combustible Dust National Emphasis Program "NEP" NRTL approved. NRTL certified US/Canada for use in hazardous locations as defined in NFPA 70.

Meets NFPA 484 Guidelines

- At Tiger-Vac® safety has no compromise

## Specifications

EXP1-IT (63L) EX (CFE) SK HEPA FOR HAZLOCS	113167A
<b>Model Name</b>	EXP1-IT (63L) EX (CFE) SK HEPA
<b>Type (Powerhead)</b>	Electric
<b>TEFC Motor</b>	Yes
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	1000 W
<b>Power</b>	1.3 HP
<b>Amperage</b>	9 A
<b>Air Flow</b>	132 CFM
<b>Vacuum Pressure</b>	69 " H <sub>2</sub> O
<b>Sound Level</b>	78/85 dB(A)
<b>Type of Power Outlet</b>	Not Included
<b>Suction Inlet Port</b>	2 "
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	None
<b>Length</b>	31 "
<b>Width</b>	24 "
<b>Height</b>	63 "
<b>Weight (Vacuum Only)</b>	168 lb.
<b>Cord Length</b>	50 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



EXP1-IT (63L) with Recovery Tank removed



Coalescing HEPA filter (Upstream) - Included



Mist Arrester Pack - Included



Liquid Level Indicator Tube - Included



Sieve Basket - Included



Cone for Interceptors - Included



Wye Connector - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included



EXP1-IT (63L) with optional Dust Extraction Arm