

Designed for use in :  
 Division 1, Class I, Groups A, B, C and D  
 Division 1, Class II, Groups E, F, G  
 Hazardous Locations as defined in the National Electrical Code (NFPA 70)

**ATEX** 3rd Party Certified

CE II 2GD  
 Ex h IIC T6 Gb  
 Ex h IIIC T85°C Db  
 LCIE 03 ATEX 6310 X



Ex h IIC T6 Gb  
 Ex h IIIC T85°C Db  
 IECEx LCIE 17.0076 X



**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.  
 We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)




Complies with NFPA 77 "Recommended Practice on Static Electricity"



### Characteristics




EX Certified



Less than 10 ohms



Dry Recovery



Wet Mix - Oil



Coalescing Filter Element



Detachable Tank



SS 304

- Hydrogen safe
- Immersion separator "Wet Oil Mix" - Meant to be used with mineral oil or any other neutralizing liquid
- **Designed for the Recovery and INERTIZATION of Conductive and Explosive Dust, such as Aluminum, Magnesium, Zirconium and other commercial alloys, into a Liquid Immersion Bath**
- Legally certified explosion proof/dust ignition proof
- Meets the requirements for a Liquid Precipitation Collector for metal dusts as outlined in NFPA 484
- Less than 10 ohms of resistivity
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency at 0.3 micron
- Pneumatic (air-operated)
- Recovery capacity of 22 lb (10 kg) of dust into 7.9 gal. (30L) of oil or any other neutralizing liquid
- Stainless steel Type 304 body and heavy duty powder coated cart
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a liquid level indicator
- Tiger-Vac® carries a large inventory of shrouded sanders, grinders and dustless drill kits, along with a large suction port for maximum dust recovery
- Tiger-Vac® recommends the use of mineral oil with a viscosity = 10.5 cSt.

---

**Tiger-Vac Inc.**  
11 SW 12th Ave #112  
Dania, FL 33004  
USA

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: 1-800-668-4437 (954-925-3625)  
Fax: 1-800-668-4439 (954-925-3626)

Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)

## Specifications

SS-IT (85L) EX (CFE) SK HEPA WET (OIL) MIX - HYDROGEN FREE	113120-OIL
<b>Model Name</b>	SS-IT (85L) EX (CFE) SK HEPA WET (OIL) MIX
<b>Type (Powerhead)</b>	Pneumatic
<b>Venturi</b>	Single
<b>Venturi (diam.)</b>	5 mm
<b>Minimum Compressor</b>	15-25 HP
<b>Air Line Size (Diam.)</b>	3/4 "
<b>Input Air Volume</b>	45 CFM
<b>Input Air Pressure</b>	80 PSI
<b>Air Flow</b>	120 CFM
<b>Vacuum Pressure</b>	120 " H <sub>2</sub> O
<b>Suction Inlet Port</b>	2 "
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	None
<b>Length</b>	40 "
<b>Width</b>	24 "
<b>Height</b>	71 "
<b>Weight (Vacuum Only)</b>	207 lb.

Please note that specifications are subject to change without notice

**Use only recommended tools & accessories**



SS-IT (85L) EX (CFE) HEPA with Recovery Tank removed



Coalescing Filter Element (CFE) - Included



Liquid Level Indicator Tube - Included



Sieve Basket - Included



Cone for Interceptors - Included




Wye Connector - Included



Suction/Airline Hose Assembly, Static Dissipative and Conductive - Included



Air Supply Hose Assembly, Static Dissipative and Conductive - Included



Rupture Disk - Optional



Optional Dust Extractor Arm