



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243

## Characteristics



Static  
Dissipating



HEPA -  
Included



Detachable  
Tank



Dry Recovery



SS 430



High Filtration  
Efficiency Unit



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Heavy duty 2-stage by-pass motor
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels

## Specifications

2D-25L (DT) MFS HEPA	111402A
<b>Model Name</b>	2D-25L (DT) MFS HEPA
<b>Type (Powerhead)</b>	Electric
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	1200 W
<b>Power</b>	1.6 HP
<b>Amperage</b>	10.5 A
<b>Air Flow</b>	110 CFM
<b>Vacuum Pressure</b>	107 " H <sub>2</sub> O
<b>Sound Level</b>	75 dB(A)
<b>Type of Power Outlet</b>	120V
<b>Suction Inlet Port</b>	2 "
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)
<b>Dust Recovery Tank</b>	6.5 Gal
<b>Length</b>	23 "
<b>Width</b>	21 "
<b>Height</b>	39.5 "
<b>Weight (Vacuum Only)</b>	50 lb.
<b>Cord Length</b>	35 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Main Cloth Filter - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38 mm) Static Dissipative Tools and Accessories -  
Optional