




Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243



### Characteristics



Dual Motor



Dry Recovery



HEPA Filter  
Available

HEPA - Optional

- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- For dry recovery only
- Can be mounted on a standard 55 gal. (209L) recovery drum
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional

## Specifications

| 4D-56 TF STD POWERHEADS     | 110949A   | 110950A  |
|-----------------------------|---|--|
| <b>Model Name</b>           | POWERHEAD MODEL 4D-56(B)TF STD DRY ONLY - NO HEPA - TOP FILL w/CLOTH FILTER | POWERHEAD MODEL 4D-56(B)TF STD HEPA - DRY ONLY - TOP FILL w/CLOTH FILTER |
| <b>Type (Powerhead)</b>     | Electric  | Electric   |
| <b>Tension</b>              | 120 V   | 120 V  |
| <b>Frequency</b>            | 60 Hz   | 60 Hz  |
| <b>Phase</b>                | Single  | Single   |
| <b>Wattage</b>              | 2040 W  | 2040 W   |
| <b>Power</b>                | 2.7 HP  | 2.7 HP   |
| <b>Amperage</b>             | 17 A  | 17 A   |
| <b>Air Flow</b>             | 200 CFM   | 200 CFM  |
| <b>Vacuum Pressure</b>      | 90 " H <sub>2</sub> O   | 90 " H <sub>2</sub> O  |
| <b>Type of Power Outlet</b> | Not Included  | Not Included   |
| <b>Cord Length</b>          | 33 ft.  | 33 ft.   |

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



HEPA Filter - Optional