

### Characteristics



Wet and  
Dry  
Recovery



HEPA Filter  
Available  
HEPA -  
Optional



- Pneumatic (air-operated). Single venturi, or twin venturi for more power
- For wet & dry recovery
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional

## Specifications

CS-12/27 POWERHEADS	211999	211999B
<b>Model Name</b>	POWERHEAD ASSEMBLY FOR MODEL CS-12 HEPA, WET & DRY	POWERHEAD ASSEMBLY FOR MODEL CS-12 NO HEPA, WET & DRY
<b>Type (Powerhead)</b>	Pneumatic	Pneumatic
<b>Venturi</b>	Single	Single
<b>Venturi (diam.)</b>	6 mm	6 mm
<b>Minimum Compressor</b>	15 HP	15 HP
<b>Air Line Size (Diam.)</b>	1/2 "	1/2 "
<b>Input Air Volume</b>	45 CFM	45 CFM
<b>Input Air Pressure</b>	80 PSI	80 PSI
<b>Air Flow</b>	120 CFM	120 CFM
<b>Vacuum Pressure</b>	170 " H <sub>2</sub> O	170 " H <sub>2</sub> O

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



HEPA Filter - Optional