

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



Characteristics



Detachable
Tank



HEPA Filter
Available



Dry Recovery

HEPA - Optional

- Electric fully automatic stand alone unit. Designed for general housekeeping applications
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Reverse Pulse System (RPS) with (1) aluminized spun bond cartridge
- Stainless steel version available
- Detachable recovery tank (DT) for easy disposal of recovered materials

Specifications

| TV-RPS 40/160L | 112876A1 | 112876A5 |
|-----------------------------|----------------------------|----------------------------|
| Model Name | TV-RPS 40/160L | TV-RPS 40/160L |
| Type (Powerhead) | Electric | Electric |
| TEFC Motor | Yes | Yes |
| Tension | 460 V | 575 V |
| Frequency | 60 Hz | 60 Hz |
| Phase | Three | Three |
| Wattage | 8000 W | 8000 W |
| Power | 11 HP | 11 HP |
| Amperage | 13 A | 10.5 A |
| Air Flow | 360 CFM | 360 CFM |
| Vacuum Pressure | 145 " H ₂ O | 145 " H ₂ O |
| VRV Setting | 120 " H ₂ O | 120 " H ₂ O |
| Type of Power Outlet | Not Included | Not Included |
| Cart Type | Detachable Tank (DT) | Detachable Tank (DT) |
| Filter Cleaning | Reverse Pulse System (RPS) | Reverse Pulse System (RPS) |
| Dust Recovery Tank | 40 Gal | 40 Gal |
| Cord Length | 30 ft. | 30 ft. |

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Reverse Pulse Cartridge - Included



TV-RPS 40/160L Back View



TV-RPS 40/160L Timer Control Box



TV-RPS 40/160L with Recovery Tank removed