

### U.S. Headquarters

Tiger-Vac Inc.  
11 SW 12th Ave #112  
Dania, FL 33004  
USA

Tel: 1-800-668-4437 (954-925-3625)  
Fax: 1-800-668-4439 (954-925-3626)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)

### International Headquarters

Tiger-Vac International Inc.  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



CLEANING MACHINES FOR  
UNCLASSIFIED (GENERAL PURPOSE)  
AREAS  
All the electrical components are certified by  
an NRTL such as UL, CSA or ETL



Continuous  
Duty



Detachable  
Tank



Dry Recovery



HEPA -  
Optional



ULPA -  
Optional



Pharma  
Applications



Cleanroom  
Compatible

## Specifications For CD-2600 CR (MRP) SERIES

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
CD-2600 CR (MRP) - P/C & S/S	111452A1	460 V	60 Hz	Three	1900 W	2.5 HP	4 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111452A2	230 V	60 Hz	Three	1900 W	2.5 HP	7 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111452A4	230 V	60 Hz	Single	1900 W	2.5 HP	7.2 A	140 CFM	111+ " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111452A5	575 V	60 Hz	Three	1900 W	2.5 HP	2.6 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111453A1	460 V	60 Hz	Three	2600 W	3.5 HP	4.7 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L34"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111453A2	230 V	60 Hz	Three	2600 W	3.5 HP	9.4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L34"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111453A5	575 V	60 Hz	Three	2600 W	3.5 HP	4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L34"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - STAINLESS STEEL	111456A1	460 V	60 Hz	Three	1900 W	2.5 HP	4 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - STAINLESS STEEL	111456A2	230 V	60 Hz	Three	1900 W	2.5 HP	7 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - STAINLESS STEEL	111456A4	230 V	60 Hz	Single	1900 W	2.5 HP	7.2 A	140 CFM	111+ " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						

<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111456A5</b>	575 V	60 Hz	Three	1900 W	2.5 HP	2.6 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										
<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111457A1</b>	460 V	60 Hz	Three	2600 W	3.5 HP	4.7 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										
<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111457A2</b>	230 V	60 Hz	Three	2600 W	3.5 HP	9.4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										
<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111457A5</b>	575 V	60 Hz	Three	2600 W	3.5 HP	4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										

Please note that specifications are subject to change without notice

## Technical Sheet For **CD-2600 CR (MRP) SERIES**

### HEPA/ULPA FILTERS AND ACCESSORIES - Optional

Part #	Description
213182	HEPA FILTER , 13.8125" x 3.875" HIGH, MINIMUM EFFICIENCY 99.995% ON 0.3 MICRON, w/GASKET INSTALLED
213181	ULPA FILTER (U15), Ø13.8125" x 3.875"(35.1cm X 98.4mm) HIGH, RATED 250 CFM
215014B	HEPA HOUSING FOR CD-2600-STD, CRS -POWDER COATED
215012	HEPA HOUSING FOR CD-2600 -STAINLESS STEEL 304

### REVERSE PURGE FILTER CARTRIDGE - Included

Part #	Description
214182A	FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD,1" PLEATS, 13 SQ.FT

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
214987	POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

### TOOLS AND ACCESSORIES - Optional

Part #	Description
500390	CLEAR URETHANE SUCTION HOSE SD* Ø2"(50mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT)
635078	CLEAR URETHANE SUCTION HOSE SD* Ø2.5"(64mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT)
500159	CLAMP, TRIDON (SCREW TYPE) SIZE 32 -STAINLESS STEEL
635016	HOSE CLAMP -STAINLESS STEEL SCREW TYPE FOR Ø2.5"(64mm)HOSE
500198	HOSE CUFF EXPANDER FOR Ø2"(50mm)VACUFLEX HOSE TO Ø2.5"(63.5mm)ADAPTOR (500168+635248)
500168	HOSE CUFF Ø2"(50mm) FOR Ø2"(50mm) VACUFLEX HOSE
635248	HOSE CUFF FOR Ø2.5"(64mm) WIRE SUPPORTED HOSE