



U.S. Headquarters

Tel: 1-800-668-4437 (954-925-3625) Fax: 1-800-668-4439 (954-925-3626) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com

International Headquarters

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2 Tel: (450-625-0099)
Fax: (450-625-3388)
Website: http://www.tiger-vac.com
Email: sales@tiger-vac.com



Tiger-Vac Inc. 11 SW 12th Ave #112 Dania, FL 33004

USA



Included









Dry Recovery

Less than 10 ohms

Specifications For CD-230V EX CFB HEPA

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet
CD-230V EX CFB	112165A4	208-230 V	60 Hz	Single	1110 W	1.5 HP	9 A	125 CFM	120 " H ₂ 0	Not Included
HEPA	Dimensions: H	59.5" x W19	" x L25" W	eight: 214 lb	. Sound	Level: 68 dE	B(A)			

Please note that specifications are subject to change without notice

Technical Sheet For CD-230V EX CFB HEPA

HEPA FILTER	TER AND ACCESSORIES - Included		
Part #	Description		
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)		

FILTERS AND	D ACCESSORIES - Included		
Part #	Description		
	MAIN FILTER ASSEMBLY w/LACES, EPITROPIC POLYESTER w/PTFE, FOR MODEL ATEX 22E (CAGE SOLD SEPARATELY)		
218390	WIRE CAGE FOR CLOTH FILTER, STAINLESS STEEL TYPE 304		

PRE-FILTER -	LTER - Optional			
Part #	Description			
217707	PRE-FILTER ASSEMBLY SD* FOR LOWER HOUSING FOR CD-120 EX / CD-2000 EX			

COLLECTION	TION FILTER BAG (CFB) - Included	
Part #	Description	
212994A- SD64	COLLECTION BAG MADE OF CONDUCTIVE MATERIAL (w/64mm COLLAR)	

TOOLS AND	LS AND ACCESSORIES - Included	
Part #	Description	
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE	
381364	DOUBLE BEND WAND ASSEMBLY (2pc) 1.5"(38mm) x 54"(137cm), STAINLESS STEEL w/ALUMINUM TOOL COUPLING	
381236	UNIVERSAL TOOL SD* w/CONDUCTIVE BRUSH STRIPS, RUBBER BLADES, BRASS AXLE & WHEELS, 1.5" x18",ALUMINUM	
381372D	CREVICE TOOL, 1.5"(38mm) x 11"(28cm), STAINLESS STEEL, FOR USE WITH HOSE CUFF WITH RING	
381185A	DUSTING BRUSH, SD*, 5"(12.5cm), ALUMINUM w/STAINLESS STEEL COUPLING #381147, w/CONDUCTIVE BRISTLES	
383461D	CONICAL NOZZLE ASSEMBLY(STRAIGHT)7.5"(19cm)CONDUCTVE RUBBER FOR HOSE CUFF W/RING (383461M+381147D)	

211065B	MULTIMETER