

U.S. Headquarters

Tiger-Vac Inc.
11 SW 12th Ave #112
Dania, FL 33004
USA

Tel: 1-800-668-4437 (954-925-3625)
Fax: 1-800-668-4439 (954-925-3626)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



CLEANING MACHINES FOR
UNCLASSIFIED (GENERAL PURPOSE)
AREAS
All the electrical components are certified by
an NRTL such as UL, CSA or ETL



Continuous Duty



Detachable Tank



Dry Recovery



HEPA - Optional



ULPA - Optional



Pharma Applications



Cleanroom Compatible

Specifications For CD-2600 CR (MRP) SERIES

| Name | Part Number | Tension | Frequency | Phase | Wattage | Power | Amperage | Air Flow | Vacuum Pressure | Type of Power Outlet | Dust Recovery Tank |
|------------------------------------|--------------------------------|---------|-----------------|--------|-----------------------|--------|----------|----------|-------------------------|----------------------|--------------------|
| CD-2600 CR (MRP) - P/C & S/S | 111452A1 | 460 V | 60 Hz | Three | 1900 W | 2.5 HP | 4 A | 148 CFM | 140 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - P/C & S/S | 111452A2 | 230 V | 60 Hz | Three | 1900 W | 2.5 HP | 7 A | 148 CFM | 140 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - P/C & S/S | 111452A4 | 230 V | 60 Hz | Single | 1900 W | 2.5 HP | 7.2 A | 140 CFM | 111+ " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - P/C & S/S | 111452A5 | 575 V | 60 Hz | Three | 1900 W | 2.5 HP | 2.6 A | 148 CFM | 140 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - P/C & S/S | 111453A1 | 460 V | 60 Hz | Three | 2600 W | 3.5 HP | 4.7 A | 219 CFM | 145 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L34" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - P/C & S/S | 111453A2 | 230 V | 60 Hz | Three | 2600 W | 3.5 HP | 9.4 A | 219 CFM | 145 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L34" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - P/C & S/S | 111453A5 | 575 V | 60 Hz | Three | 2600 W | 3.5 HP | 4 A | 219 CFM | 145 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L34" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - STAINLESS STEEL | 111456A1 | 460 V | 60 Hz | Three | 1900 W | 2.5 HP | 4 A | 148 CFM | 140 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - STAINLESS STEEL | 111456A2 | 230 V | 60 Hz | Three | 1900 W | 2.5 HP | 7 A | 148 CFM | 140 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |
| CD-2600 CR (MRP) - STAINLESS STEEL | 111456A4 | 230 V | 60 Hz | Single | 1900 W | 2.5 HP | 7.2 A | 140 CFM | 111+ " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" | | Weight: 247 lb. | | Sound Level: 68 dB(A) | | | | | | |

| | | | | | | | | | | | |
|---|--|-------|-------|-------|--------|--------|-------|---------|------------------------|--------------|---------|
| CD-2600 CR (MRP) - STAINLESS STEEL | 111456A5 | 575 V | 60 Hz | Three | 1900 W | 2.5 HP | 2.6 A | 148 CFM | 140 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |
| CD-2600 CR (MRP) - STAINLESS STEEL | 111457A1 | 460 V | 60 Hz | Three | 2600 W | 3.5 HP | 4.7 A | 219 CFM | 145 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |
| CD-2600 CR (MRP) - STAINLESS STEEL | 111457A2 | 230 V | 60 Hz | Three | 2600 W | 3.5 HP | 9.4 A | 219 CFM | 145 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |
| CD-2600 CR (MRP) - STAINLESS STEEL | 111457A5 | 575 V | 60 Hz | Three | 2600 W | 3.5 HP | 4 A | 219 CFM | 145 " H ₂ O | Not Included | 9.5 Gal |
| | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |

Please note that specifications are subject to change without notice

Technical Sheet For CD-2600 CR (MRP) SERIES

HEPA/ULPA FILTERS AND ACCESSORIES - Optional

| Part # | Description |
|---------|--|
| 213182 | HEPA FILTER , 13.8125" x 3.875" HIGH, MINIMUM EFFICIENCY 99.995% ON 0.3 MICRON, w/GASKET INSTALLED |
| 213181 | ULPA FILTER (U15), Ø13.8125" x 3.875"(35.1cm X 98.4mm) HIGH, RATED 250 CFM |
| 215014B | HEPA HOUSING FOR CD-2600-STD, CRS -POWDER COATED |
| 215012 | HEPA HOUSING FOR CD-2600 -STAINLESS STEEL 304 |

REVERSE PURGE FILTER CARTRIDGE - Included

| Part # | Description |
|---------|---|
| 214182A | FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD,1" PLEATS, 13 SQ.FT |

POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

| Part # | Description |
|--------|--|
| 214987 | POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5) |
| 213780 | POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP) |

TOOLS AND ACCESSORIES - Optional

| Part # | Description |
|--------|---|
| 500390 | CLEAR URETHANE SUCTION HOSE SD* Ø2"(50mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT) |
| 635078 | CLEAR URETHANE SUCTION HOSE SD* Ø2.5"(64mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT) |
| 500159 | CLAMP, TRIDON (SCREW TYPE) SIZE 32 -STAINLESS STEEL |
| 635016 | HOSE CLAMP -STAINLESS STEEL SCREW TYPE FOR Ø2.5"(64mm)HOSE |
| 500198 | HOSE CUFF EXPANDER FOR Ø2"(50mm)VACUFLEX HOSE TO Ø2.5"(63.5mm)ADAPTOR (500168+635248) |
| 500168 | HOSE CUFF Ø2"(50mm) FOR Ø2"(50mm) VACUFLEX HOSE |
| 635248 | HOSE CUFF FOR Ø2.5"(64mm) WIRE SUPPORTED HOSE |