C-10 EX (4W) STAINLESS STEEL ULPA

Technical Sheet



U.S. Headquarters

Tel: 1-800-668-4437 (954-925-3625) Fax: 1-800-668-4439 (954-925-3626) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com **International Headquarters**

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2 Tel: (450-625-0099)
Fax: (450-625-3388)
Website: http://www.tiger-vac.com
Email: sales@tiger-vac.com



Tiger-Vac Inc.

Dania, FL 33004 USA

11 SW 12th Ave #112



DUST IGNITION PROTECTED

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)

Division 2, Class II, Groups F and G







High Filtration Static Efficiency Unit Dissipating



Stainless General



SD Accessories Dry Recovery
- Included



Groups F and G Cleanroom Compatible Dust (Combustible and Toxic/Nuisance) IIIB Cleanroom Compatible Dust (Combustible and Toxic/Nuisance)

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Complies with NFPA 77 "Recommended Practice on Static Electricity"



IECEx 3rd Party Certified External: Ex h tc IIIC T200°C Dc IP6X Internal: Ex h IIIC T200°C Da IECEx LCIE 15.0048

Specifications For C-10 EX (4W) STAINLESS STEEL ULPA

Nam	1е	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dry Recovery - Disposable Filter Bag
C-10 EX STAINLI	` '	110540A	120 V	60 Hz	Single	1207 W	1.6 HP	10.5 A	110 CFM	107 " H ₂ 0	120V	5 gal.
STEEL (ULPA	Dimensions:	H34.5" x V	V18" x L19"	Weight:	66 lb.	Sound Lev	el: 75 dB(A)				
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary. With stainless steel tank.												

C-10 EX (4W) STAINLESS	110540A- BLSD	120 V	60 Hz	Single	1100 W	1.5 HP	13 A	127 CFM	89 " H ₂ 0	120V	5 gal.
STEEL ULPA BLSD	Dimensions: H34.5" x W18" x L19" Weight: 66 lb. Sound Level: 75 dB(A)										
Description: With Brushless Motor											

Please note that specifications are subject to change without notice

Technical Sheet For C-10 EX (4W) STAINLESS STEEL ULPA

HEPA/ULPA	HEPA/ULPA FILTERS AND ACCESSORIES - Included					
Part #	Description					
211854	HEPA FILTER (H14) WITH GASKET, 2"(50mm) HIGH					
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION					
219372	ULPA FILTER WITH GASKETS ON BOTH SIDES, 99.999% ON 0.12 MICRON, FOR MODELS CR-1300 & CR-1400					

FILTERS AND ACCESSORIES - Included

Part #	Description
215393-SD	MAIN FILTER ASSEMBLY, EPITROPIC POLYESTER WITH STAINLESS STEEL BANDS
212244A	SD* MICRO SAFETY FILTER (EPITROPIC POLYESTER w/PTFE) ASSEMBLY WITH CLAMP

CONDUCTIVE RECOVERY BAG - Included				
Part #	Description			
212994- SD64	COLLECTION BAG MADE OF CONDUCTIVE MATERIAL w/64mm COLLAR (PACKAGE OF 3)			

POLY LINE	Y LINER RECOVERY BAGS AND ACCESSORIES - Included						
Part #	Description						
212100	CONDUCTIVE POLY LINER FOR 10 GALLON TANK, NO HOLE (INCLUDES TWIST TIE)						

TOOLS AND ACCESSORIES - Included					
Part #	Description				
323403D	CLEAR URETHANE HOSE ASSEMBLY 1.25"(32mm)x10'(3m) WITH SS CURVED HANDLE & 2"(50mm) FEMALE CAMLOCK SS				
323330	EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2)				
323412	FLOOR TOOL ASSEMBLY, AUTOCLAVABLE, 1.25"(32mm) x 12"(30cm), STAINLESS STEEL w/WHITE NITRILE BLADES				
323413	CREVICE TOOL, AUTOCLAVABLE, Ø1.25"(32mm)x10"(25.4cm) -STAINLESS STEEL				
323564	CONICAL NOZZLE ONLY WITH CURVED TIP, Ø1.25"(32mm)x10"(25cm) CLEAR FOODGRADE SILICONE				

SPECIAL SU	SPECIAL SUCTION HOSES - Optional				
Part #	Description				
323470	FOODGRADE HOSE ASSEMBLY 1.25"(32mm)x10'(3m) FOR CWR-XX (SMOOTH INSIDE & OUT)				
323455	EPDM HOSE ASSEMBLY SD* AUTOCLAVABLE 1.25" x 10' (32mm x3m) w/1.5" s/S SWIVEL CAMLOCK & CURVED HANDLE				

NEEDLE TRAP AND ACCESSORIES - Optional					
Part #	Description				
215500	NEEDLE TRAP ASSEMBLY, STAINLESS STEEL, 2"(50mm) INLET X 1.25"(32mm) OUTLET, ELECTROPOLISHED				
500235M	TIGER-CLAW ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x4.5"(11.5cm)				
500231M	CONICAL NOZZLE ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x7.5"(19cm)				