

CD-EX Models Certified for:

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)

Division 1, Class I, Group D and Class II, Groups F and G, T3C
 Division 1, Class II Group E (metal dust) motor and switch available

Division 2, Class I Group D and Class II, Groups F and G, T3C

CD EX Series **IECEX** 3rd Party Certified

Ex d IIB T4 Gb

Ex t IIIC T135°C Db IP65

IECEX LCI 10.0040 X

Certified for providing an Equipment Protection Level of EPL Db and EPL Gb



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.


We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Complies with NFPA 77 "Recommended Practice on Static Electricity"

Characteristics



EX Certified



Less than 10 ohms



Cleanroom Compatible



Pharma Applications



Continuous Duty



Dry Recovery



SS 304



Detachable Tank



HEPA Filter Available



ULPA - Included

HEPA - Optional



- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- Continuous duty single phase or 3-phase (TEFC) explosion proof/dust ignition proof motor
- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Muffler assembly, made of stainless steel with sound insulating foam to ensure quiet operation, is included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- Manual Reverse Purge (MRP) with static dissipative reverse purge cartridge
- Static conductive aluminized spun bond reverse purge cartridge is contained within a removable filter chamber
- All stainless steel Type 304 construction
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Static dissipative poly liner and clip for the easy and safe disposal of recovered materials - available
- Vertical mounting for areas with space constraints
- Equipped with a Carriage with Suspended Motor Top

(CSMT) and tool basket. Includes static dissipative wheels

- Optional Ø1.5" (Ø38 mm) or Ø2" (Ø50 mm) tools & accessories
- Motor and switch for use in the presence of conductive metal dust is available. North-America: Class II, Group E Europe: Dust Group III C
- Other motor performances available

Specifications

CD/EUR-36L EX DT (MRP) ULPA WITH SS CART	112157A1-SS	112157A2-SS	112157A5-SS	112158A3-SS	112159A3-SS	112160A1-SS
Model Name	CD/EUR-36L EX DT (MRP) ULPA WITH SS CART CLASS I - GROUP D, CLASS II - GROUPS F & G	CD/EUR-36L EX DT (MRP) ULPA WITH SS CART CLASS I - GROUP D, CLASS II - GROUPS F & G	CD/EUR-36L EX DT (MRP) ULPA WITH SS CART CLASS I - GROUP D, CLASS II - GROUPS F & G	CD/EUR-36L EX DT (MRP) ULPA WITH SS CART CLASS I - GROUP D, CLASS II - GROUPS F & G	CD/EUR-36L EX DT (MRP) ULPA WITH SS CART CLASS I - GROUP D, CLASS II - GROUPS F & G	CD/EUR-36L EX DT (MRP) ULPA WITH SS CART CLASS I - GROUP D, CLASS II - GROUPS E, F & G
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Tension	460 V	230 V	575 V	120 V	120 V	460 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Three	Single	Single	Three
Wattage	1480 W	1480 W	1480 W	1110 W	1110 W	1480 W
Power	2 HP	2 HP	2 HP	1.5 HP	1.5 HP	2 HP
Amperage	2.6 A	5.2 A	2.1 A	15 A	15 A	2.6 A
Air Flow	158 CFM	158 CFM	158 CFM	125 CFM	125 CFM	158 CFM
Vacuum Pressure	130 " H ₂ O	130 " H ₂ O	130 " H ₂ O	120 " H ₂ O	120 " H ₂ O	130 " H ₂ O
VRV Setting	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O	80 " H ₂ O
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet Port	2 "	2 "	2 "	2 "	2 "	2 "
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
Length	30.5 "	30.5 "	30.5 "	30.5 "	30.5 "	30.5 "
Width	22 "	22 "	22 "	22 "	22 "	22 "
Height	70 "	70 "	70 "	70 "	70 "	70 "
Weight (Vacuum Only)	218 lb.	218 lb.	218 lb.	218 lb.	218 lb.	218 lb.
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.
CD/EUR-36L EX DT (MRP) ULPA WITH SS CART	112160A2-SS	112160A5-SS				
Model Name	CD/EUR-36L EX DT (MRP) ULPA CLASS I - GROUP D, CLASS II - GROUPS E, F & G	CD/EUR-36L EX DT (MRP) ULPA CLASS I - GROUP D, CLASS II - GROUPS E, F & G				
Type (Powerhead)	Electric	Electric				
TEFC Motor	Yes	Yes				
Tension	230 V	575 V				

Frequency	60 Hz	60 Hz
Phase	Three	Three
Wattage	1480 W	1480 W
Power	2 HP	2 HP
Amperage	5.2 A	2.1 A
Air Flow	158 CFM	158 CFM
Vacuum Pressure	130 " H ₂ O	130 " H ₂ O
VRV Setting	80 " H ₂ O	80 " H ₂ O
Type of Power Outlet	Not Included	Not Included
Suction Inlet Port	2 "	2 "
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	9.5 Gal	9.5 Gal
Length	30.5 "	30.5 "
Width	22 "	22 "
Height	70 "	70 "
Weight (Vacuum Only)	218 lb.	218 lb.
Cord Length	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Ø1.5" (Ø38 mm) Static Dissipative Tools and Accessories - Optional



Ø2" (Ø50 mm) Static Dissipative Tools and Accessories - Optional



Conductive Aluminized Spun Bond Reverse Purge Cartridge (shown with and without optional skirt) - Included



ULPA Filter - Included



CD/EUR-36L EX DT (MRP) ULPA with Recovery Tank and Filter Chamber removed