

### Characteristics



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed for the recovery of acids and corrosive liquids
- EMI/RFI Shielded
- Heavy duty 2-stage by-pass motor
- Available with a variety of activated carbon, including KINA 3® activated carbon for the adsorption of chloride and acid vapors (HF, HCL, etc). Other types of activated carbon are available. Carbon cartridges must be ordered separately - not included
- For liquid recovery
- Acid-resistant polyethylene, nylon and PVC
- Includes a complete tool kit.

## Specifications

CWR-ARU-15 (TC) POLY MRAC	110511A
<b>Model Name</b>	CWR-ARU-15 (TC) POLY MRAC
<b>Type (Powerhead)</b>	Electric
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	1200 W
<b>Power</b>	1.6 HP
<b>Amperage</b>	10.5 A
<b>Air Flow</b>	110 CFM
<b>Vacuum Pressure</b>	107 " H <sub>2</sub> O
<b>Sound Level</b>	75 dB(A)
<b>Type of Power Outlet</b>	120V
<b>Cart Type</b>	Tilt Cart (TC)
<b>Filter Cleaning</b>	None
<b>Liquid Recovery Capacity</b>	12.5 gal.
<b>Length</b>	27 "
<b>Width</b>	30 "
<b>Height</b>	48 "
<b>Weight (Vacuum Only)</b>	108 lb.
<b>Cord Length</b>	35 ft.

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



ULPA Filter - Included



Liquid Filter - Included



ARU STD Tools and Accessories - Included



Activated Carbon Cartridge - Optional