

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



Characteristics




Continuous Duty



Detachable Tank



Dry Recovery



HEPA Filter Available

HEPA - Optional



ULPA Filter Available

ULPA - Optional



Pharma Applications



Cleanroom Compatible

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- Designed to be attached to process machines and for general cleanup in the Food industry
- Can also be used for the recovery of tablets in the Pharmaceutical industry
- Continuous duty single phase or 3-phase motor mounted vertically
- Manual Reverse Purge (MRP) with static dissipative reverse purge cartridge
- Available in a fixed or mobile unit
- For dry recovery only
- Available in stainless steel, white powder coated or stainless steel & white powder coated versions
- Vertical mounting for areas with space constraints
- 4 wheels for easy maneuverability

Specifications

CD-2600 CR (MRP) SERIES	111452A1	111452A2	111452A4	111452A5	111453A1	111453A2
Model Name	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Tension	460 V	230 V	230 V	575 V	460 V	230 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Single	Three	Three	Three
Wattage	1900 W	1900 W	1900 W	1900 W	2600 W	2600 W
Power	2.5 HP	2.5 HP	2.5 HP	2.5 HP	3.5 HP	3.5 HP
Amperage	4 A	7 A	7.2 A	2.6 A	4.7 A	9.4 A
Air Flow	148 CFM	148 CFM	140 CFM	148 CFM	219 CFM	219 CFM
Vacuum Pressure	140 " H ₂ O	140 " H ₂ O	111+ " H ₂ O	140 " H ₂ O	145 " H ₂ O	145 " H ₂ O
VRV Setting	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet Port	2 "	2 "	2 "	2 "	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
Length	26 "	26 "	26 "	26 "	34 "	34 "
Width	20 "	20 "	20 "	20 "	20 "	20 "
Height	75 "	75 "	75 "	75 "	75 "	75 "
Weight (Vacuum Only)	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.
CD-2600 CR (MRP) SERIES	111453A5	111456A1	111456A2	111456A4	111456A5	111457A1
Model Name	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Tension	575 V	460 V	230 V	230 V	575 V	460 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Three	Single	Three	Three
Wattage	2600 W	1900 W	1900 W	1900 W	1900 W	2600 W
Power	3.5 HP	2.5 HP	2.5 HP	2.5 HP	2.5 HP	3.5 HP
Amperage	4 A	4 A	7 A	7.2 A	2.6 A	4.7 A

Air Flow	219 CFM	148 CFM	148 CFM	140 CFM	148 CFM	219 CFM
Vacuum Pressure	145 " H ₂ O	140 " H ₂ O	140 " H ₂ O	111+ " H ₂ O	140 " H ₂ O	145 " H ₂ O
VRV Setting	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Suction Inlet Port	2 "	2 "	2 "	2 "	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
Length	34 "	26 "	26 "	26 "	26 "	26 "
Width	20 "	20 "	20 "	20 "	20 "	20 "
Height	75 "	75 "	75 "	75 "	75 "	75 "
Weight (Vacuum Only)	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.

CD-2600 CR (MRP) SERIES	111457A2	111457A5
Model Name	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL
Type (Powerhead)	Electric	Electric
TEFC Motor	Yes	Yes
Tension	230 V	575 V
Frequency	60 Hz	60 Hz
Phase	Three	Three
Wattage	2600 W	2600 W
Power	3.5 HP	3.5 HP
Amperage	9.4 A	4 A
Air Flow	219 CFM	219 CFM
Vacuum Pressure	145 " H ₂ O	145 " H ₂ O
VRV Setting	110 " H ₂ O	110 " H ₂ O
Sound Level	68 dB(A)	68 dB(A)
Type of Power Outlet	Not Included	Not Included
Suction Inlet Port	2 "	2 "
Cart Type	Carriage Base (CB)	Carriage Base (CB)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	9.5 Gal	9.5 Gal
Length	26 "	26 "

Width	20 "	20 "
Height	75 "	75 "
Weight (Vacuum Only)	247 lb.	247 lb.
Cord Length	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



CD-2600 Next to average sized man



CD-2600 Rear View



CD-2600 with Recovery Tank removed



Conductive Aluminized Spun Bond Reverse Purge Cartridge
(shown with and without optional skirt) - Included



HEPA Filter - Optional