

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL



### Characteristics



Continuous Duty



Detachable Tank




Dry Recovery



HEPA Filter Available

HEPA - Optional



ULPA Filter Available

ULPA - Optional



Pharma Applications



Cleanroom Compatible

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- Designed to be attached to process machines and for general cleanup in the Food industry
- Can also be used for the recovery of tablets in the Pharmaceutical industry
- Continuous duty single phase or 3-phase motor mounted vertically
- Manual Reverse Purge (MRP) with static dissipative reverse purge cartridge
- Available in a fixed or mobile unit
- For dry recovery only
- Available in stainless steel, white powder coated or stainless steel & white powder coated versions
- Vertical mounting for areas with space constraints
- 4 wheels for easy maneuverability

## Specifications

CD-2600 CR (MRP) SERIES	111452A1	111452A2	111452A4	111452A5	111453A1	111453A2
<b>Model Name</b>	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - P/C & S/S
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Tension</b>	460 V	230 V	230 V	575 V	460 V	230 V
<b>Frequency</b>	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
<b>Phase</b>	Three	Three	Single	Three	Three	Three
<b>Wattage</b>	1900 W	1900 W	1900 W	1900 W	2600 W	2600 W
<b>Power</b>	2.5 HP	2.5 HP	2.5 HP	2.5 HP	3.5 HP	3.5 HP
<b>Amperage</b>	4 A	7 A	7.2 A	2.6 A	4.7 A	9.4 A
<b>Air Flow</b>	148 CFM	148 CFM	140 CFM	148 CFM	219 CFM	219 CFM
<b>Vacuum Pressure</b>	140 " H <sub>2</sub> O	140 " H <sub>2</sub> O	111+ " H <sub>2</sub> O	140 " H <sub>2</sub> O	145 " H <sub>2</sub> O	145 " H <sub>2</sub> O
<b>VRV Setting</b>	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O
<b>Sound Level</b>	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
<b>Type of Power Outlet</b>	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
<b>Suction Inlet Port</b>	2 "	2 "	2 "	2 "	2 "	2 "
<b>Cart Type</b>	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
<b>Filter Cleaning</b>	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
<b>Dust Recovery Tank</b>	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
<b>Length</b>	26 "	26 "	26 "	26 "	34 "	34 "
<b>Width</b>	20 "	20 "	20 "	20 "	20 "	20 "
<b>Height</b>	75 "	75 "	75 "	75 "	75 "	75 "
<b>Weight (Vacuum Only)</b>	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.
<b>Cord Length</b>	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.
CD-2600 CR (MRP) SERIES	111453A5	111456A1	111456A2	111456A4	111456A5	111457A1
<b>Model Name</b>	CD-2600 CR (MRP) - P/C & S/S	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes	Yes	Yes	Yes	Yes
<b>Tension</b>	575 V	460 V	230 V	230 V	575 V	460 V
<b>Frequency</b>	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
<b>Phase</b>	Three	Three	Three	Single	Three	Three
<b>Wattage</b>	2600 W	1900 W	1900 W	1900 W	1900 W	2600 W
<b>Power</b>	3.5 HP	2.5 HP	2.5 HP	2.5 HP	2.5 HP	3.5 HP
<b>Amperage</b>	4 A	4 A	7 A	7.2 A	2.6 A	4.7 A

<b>Air Flow</b>	219 CFM	148 CFM	148 CFM	140 CFM	148 CFM	219 CFM
<b>Vacuum Pressure</b>	145 " H <sub>2</sub> O	140 " H <sub>2</sub> O	140 " H <sub>2</sub> O	111+ " H <sub>2</sub> O	140 " H <sub>2</sub> O	145 " H <sub>2</sub> O
<b>VRV Setting</b>	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O
<b>Sound Level</b>	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)	68 dB(A)
<b>Type of Power Outlet</b>	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
<b>Suction Inlet Port</b>	2 "	2 "	2 "	2 "	2 "	2 "
<b>Cart Type</b>	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)	Carriage Base (CB)
<b>Filter Cleaning</b>	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
<b>Dust Recovery Tank</b>	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal	9.5 Gal
<b>Length</b>	34 "	26 "	26 "	26 "	26 "	26 "
<b>Width</b>	20 "	20 "	20 "	20 "	20 "	20 "
<b>Height</b>	75 "	75 "	75 "	75 "	75 "	75 "
<b>Weight (Vacuum Only)</b>	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.	247 lb.
<b>Cord Length</b>	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.

<b>CD-2600 CR (MRP) SERIES</b>	<b>111457A2</b>	<b>111457A5</b>
<b>Model Name</b>	CD-2600 CR (MRP) - STAINLESS STEEL	CD-2600 CR (MRP) - STAINLESS STEEL
<b>Type (Powerhead)</b>	Electric	Electric
<b>TEFC Motor</b>	Yes	Yes
<b>Tension</b>	230 V	575 V
<b>Frequency</b>	60 Hz	60 Hz
<b>Phase</b>	Three	Three
<b>Wattage</b>	2600 W	2600 W
<b>Power</b>	3.5 HP	3.5 HP
<b>Amperage</b>	9.4 A	4 A
<b>Air Flow</b>	219 CFM	219 CFM
<b>Vacuum Pressure</b>	145 " H <sub>2</sub> O	145 " H <sub>2</sub> O
<b>VRV Setting</b>	110 " H <sub>2</sub> O	110 " H <sub>2</sub> O
<b>Sound Level</b>	68 dB(A)	68 dB(A)
<b>Type of Power Outlet</b>	Not Included	Not Included
<b>Suction Inlet Port</b>	2 "	2 "
<b>Cart Type</b>	Carriage Base (CB)	Carriage Base (CB)
<b>Filter Cleaning</b>	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
<b>Dust Recovery Tank</b>	9.5 Gal	9.5 Gal
<b>Length</b>	26 "	26 "

<b>Width</b>	20 "	20 "
<b>Height</b>	75 "	75 "
<b>Weight (Vacuum Only)</b>	247 lb.	247 lb.
<b>Cord Length</b>	50 ft.	50 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



CD-2600 Next to average sized man



CD-2600 Rear View



CD-2600 with Recovery Tank removed



Conductive Aluminized Spun Bond Reverse Purge Cartridge  
(shown with and without optional skirt) - Included



HEPA Filter - Optional