

CD-2600 CR (ARP) SERIES

Technical Sheet

Tiger-Vac Inc. 11 SW 12th Ave #112 Dania, FL 33004 USA

U.S. Headquarters

Tel: 1-800-668-4437 (954-925-3625) Fax: 1-800-668-4439 (954-925-3626) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2

International Headquarters

Fax: (450-625-3388) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com



CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS

All the electrical components are certified by an NRTL such as UL, CSA or ETL

Continuous Detachable

Tank



Cleanroom Compatible Tel: (450-625-0099)



HEPA -

Optional

Dry Recovery



ULPA -Optional Applications

Specifications For CD-2600 CR (ARP) SERIES

| Name | Part Number | Tension | Frequency | Phase | Wattage | Power | Amperage | Air Flow | Vacuum Pressure | Type of Power Outlet | Dust Recovery Tank | |
|-----------------------------|--|-----------|---------------------------------------|---------------------------------------|---------|------------|--------------|------------|----------------------------|-------------------------|--------------------------|--|
| CD-2600 CR (ARP) - P/C & | 111472A1 | 460 V | 60 Hz | Three | 1900 W | 2.5 HP | 4 A | 148 CFM | 140 " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | | |
| CD-2600 CR (ARP) - P/C & | 111472A2 | 230 V | 60 Hz | Three | 1900 W | 2.5 HP | 7 A | 148 CFM | 140 " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: | 0" x L26" | Weight: 2 | Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | |
| CD-2600 CR (ARP) - P/C & | 111472A4 | 230 V | 60 Hz | Single | 1900 W | 2.5 HP | 7.2 A | 140 CFM | 111+ " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: | H75" x W2 | 0" x L26" | Weight: 2 | 47 lb. | Sound Leve | el: 68 dB(A) | | | | | |
| CD-2600 CR (ARP) - P/C & | 111472A5 | 575 V | 60 Hz | Three | 1900 W | 2.5 HP | 2.6 A | 148 CFM | 140 " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | | |
| CD-2600 CR (ARP) - P/C & | 111473A1 | 460 V | 60 Hz | Three | 2600 W | 3.5 HP | 4.7 A | 219 CFM | 145 " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | | |
| CD-2600 CR (ARP) - P/C & | 111473A2 | 230 V | 60 Hz | Three | 2600 W | 3.5 HP | 9.4 A | 219 CFM | 145 " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | | |
| CD-2600 CR (ARP) - P/C & | 111473A5 | 575 V | 60 Hz | Three | 2600 W | 3.5 HP | 4 A | 219 CFM | 145 " H ₂ 0 | Not Included | 9.5 Gal | |
| S/S | Dimensions: | H75" x W2 | 0" x L26" | Weight: 247 lb. Sound Level: 68 dB(| | | el: 68 dB(A) | () | | | | |
| CD-2600 CR (ARP) - | 111476A1 | 460 V | 60 Hz | Three | 1900 W | 2.5 HP | 4 A | 148 CFM | 140 " H ₂ 0 | Not Included | 9.5 Gal | |
| STAINLESS STEEL | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | | |
| CD-2600 CR (ARP) - | 111476A2 | 230 V | 60 Hz | Three | 1900 W | 2.5 HP | 7 A | 148 CFM | 140 " H ₂ 0 | Not Included | 9.5 Gal | |
| STAINLESS STEEL | Dimensions: | 0" x L26" | Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | |
| CD-2600 CR (ARP) - | 111476A4 | 230 V | 60 Hz | Single | 1900 W | 2.5 HP | 7.2 A | 140 CFM | 111+ " H ₂ 0 | Not Included | 9.5 Gal | |
| STAINLESS STEEL | Dimensions: | H75" x W2 | :0" x L26" | Weight: 2 | 47 lb. | Sound Leve | el: 68 dB(A) | | | | | |

| CD-2600 CR (ARP) - | 111476A5 | 575 V | 60 Hz | Three | 1900 W | 2.5 HP | 2.6 A | 148 CFM | 140 " H ₂ 0 | Not Included | 9.5 Gal |
|-----------------------|--|-----------|------------|-----------|----------|------------|--------------|------------|---------------------------|-----------------|---------|
| STAINLESS STEEL | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |
| CD-2600 CR (ARP) - | 111477A1 | 460 V | 60 Hz | Three | 2600 W | 3.5 HP | 4.7 A | 219 CFM | 145 " H ₂ 0 | Not Included | 9.5 Gal |
| STAINLESS STEEL | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |
| CD-2600 CR (ARP) - | 111477A2 | 230 V | 60 Hz | Three | 2600 W | 3.5 HP | 9.4 A | 219 CFM | 145 " H ₂ 0 | Not Included | 9.5 Gal |
| STAINLESS STEEL | Dimensions: H75" x W20" x L26" Weight: 247 lb. Sound Level: 68 dB(A) | | | | | | | | | | |
| CD-2600 CR | 111477A5 | 575 V | 60 Hz | Three | 2600 W | 3.5 HP | 4 A | 219 | 145 " | Not | 9.5 Gal |
| (ARP) - | 1114//A3 | 575 V | 00 112 | 111120 | 2000 W | 5.5 HP | 47 | CFM | H ₂ 0 | Included | 9.5 Gal |
| STAINLESS STEEL | Dimensions: | H75" x W2 | 20" x L26" | Weight: 2 | 47 lb. S | Sound Leve | el: 68 dB(A) | | | | |

Please note that specifications are subject to change without notice

Technical Sheet For CD-2600 CR (ARP) SERIES

| HEPA/UL | HEPA/ULPA FILTERS AND ACCESSORIES - Optional | | | | | | |
|---------|--|--|--|--|--|--|--|
| Part # | Description | | | | | | |
| 213182 | HEPA FILTER , 13.8125" x 3.875" HIGH, MINIMUM EFFICIENCY 99.995% ON 0.3 MICRON, w/GASKET INSTALLED | | | | | | |
| 213181 | ULPA FILTER (U15), Ø13.8125" x 3.875"(35.1cm X 98.4mm) HIGH, RATED 250 CFM | | | | | | |
| 215014B | HEPA HOUSING FOR CD-2600-STD, CRS -POWDER COATED | | | | | | |
| 215012 | HEPA HOUSING FOR CD-2600 -STAINLESS STEEL 304 | | | | | | |

REVERSE PURGE FILTER CARTRIDGE - Included

Part # Description

214182A FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD,1" PLEATS, 13 SQ.FT

| POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional | | | | | |
|---|--|--|--|--|--|
| Part # | Description | | | | |
| 214987 | POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5) | | | | |
| 213780 | POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP) | | | | |
| | | | | | |

| TOOLS A | TOOLS AND ACCESSORIES - Optional | | | | | |
|---------|---|--|--|--|--|--|
| Part # | Description | | | | | |
| 500390 | CLEAR URETHANE SUCTION HOSE SD* Ø2"(50mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT) | | | | | |
| 635078 | CLEAR URETHANE SUCTION HOSE SD* Ø2.5"(64mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT) | | | | | |
| 500159 | CLAMP, TRIDON (SCREW TYPE) SIZE 32 -STAINLESS STEEL | | | | | |
| 635016 | HOSE CLAMP -STAINLESS STEEL SCREW TYPE FOR Ø2.5"(64mm)HOSE | | | | | |
| 500198 | HOSE CUFF EXPANDER FOR Ø2"(50mm)VACUFLEX HOSE TO Ø2.5"(63.5mm)ADAPTOR (500168+635248) | | | | | |
| 500168 | HOSE CUFF Ø2"(50mm) FOR Ø2"(50mm) VACUFLEX HOSE | | | | | |
| 635248 | HOSE CUFF FOR Ø2.5"(64mm) WIRE SUPPORTED HOSE | | | | | |