



DUST IGNITION PROTECTED

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)

Division 2, Class II, Groups F and G

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Complies with NFPA 77 "Recommended Practice on Static Electricity"

Characteristics



HEPA - Included



High Filtration Efficiency Unit



Detachable Tank



Dry Recovery



Dual Motor



Static Dissipating



SS 430



SD Accessories - Included



- **The most flexible industrial cleaning tool a firing range can use:**
- For housekeeping and general cleaning of firing ranges
- Can safely recover lead dust and unspent gunpowder
- Dual bypass/dual speed Ametek® long life motors
- Includes 5 HEPA filters. Class H14. Individually factory tested
- Stainless steel Type 430 body and recovery tank
- Manual Filter Shaker (MFS) with static dissipative Teflon laminated main cloth filter assembly
- Detachable filter chamber and recovery tank for easy disposal of contaminated recovered materials
- Material to be recovered within a conductive poly liner recovery bag for easy disposal
- Front mounted 28" (71 cm) floor tool is included
- The onboard SIDEKICK hose and wand are designed to improve the overall cleaning efficiency resulting in improved productivity
- Ideal for cleaning along vertical surfaces, removing debris from cracks and crevices, stray small caliber casings and those difficult to reach nooks and crannies in the bullet trap
- Dual suction inlets with gate valves allow the operator to easily "Shift and Go" and switch from wide area floor cleaning to spot cleaning with our "SIDEKICK" hose and wand

Specifications

4D-35L EX DT MFS HEPA (FRP-SIDEKICK)	113308A
Model Name	4D-35L EX DT MFS HEPA (FRP-SIDEKICK)
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	2040 W
Power	2.7 HP
Amperage	15.2 A
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ O
Type of Power Outlet	20 Amps
Suction Inlet Port	Two x 2"
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	9.2 Gal
Length	43 "
Width	29 "
Height	54.5 "
Weight (Vacuum Only)	125 lb.
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



4D-35LEX Suspended Powerhead



Detachable Filter Chamber and Recovery Tank for easy decontamination



4D-35LEX DT MFS HEPA with Recovery Tank removed



Dual Suction Inlets with Gate Valves and Manual Filter Shaker (MFS)



HEPA Filter - Included



Main Cloth Filter and Cage, Static Dissipative - Included



Conductive Polyliner Recovery Bag - Included



SideKick Static Conductive Suction Hose, Wand and Conical Nozzle - Included



Front Mount Floor Tool - Included