



DUST IGNITION PROTECTED

CLEANING MACHINES For Hazardous Locations (Classes C1618 01 & C1618 81)

Division 2, Class II, Groups F and G

**ESD Safe** Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Complies with NFPA 77 "Recommended Practice on Static Electricity"

### Characteristics



HEPA - Included



High Filtration Efficiency Unit



Detachable Tank



Dry Recovery



Dual Motor



Static Dissipating



SS 430



SD Accessories - Included



- ***Our most popular unit for firing range housekeeping***
- Ideal for housekeeping and general cleaning
- Dual bypass/dual speed Ametek® long life motors
- Includes 5 HEPA filters. Class H14. Individually factory tested
- Stainless steel Type 430 body and recovery tank
- Manual Filter Shaker (MFS) with static dissipative Teflon laminated main cloth filter assembly
- Detachable filter chamber and recovery tank for easy disposal of contaminated recovered materials
- Material to be recovered within a conductive poly liner recovery bag for easy disposal
- Front mounted 28" (71 cm) floor tool designed for Firing Ranges, is ideal for larger surfaces in hazardous locations/areas - optional

## Specifications

4D-35L EX DT MFS HEPA (FRP)	113306A
<b>Model Name</b>	4D-35L EX DT MFS HEPA (FRP)
<b>Type (Powerhead)</b>	Electric
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	2040 W
<b>Power</b>	2.7 HP
<b>Amperage</b>	15.2 A
<b>Air Flow</b>	200 CFM
<b>Vacuum Pressure</b>	90 " H <sub>2</sub> O
<b>Type of Power Outlet</b>	20 Amps
<b>Suction Inlet Port</b>	2 "
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)
<b>Dust Recovery Tank</b>	9.2 Gal
<b>Length</b>	28 "
<b>Width</b>	23.5 "
<b>Height</b>	54.5 "
<b>Weight (Vacuum Only)</b>	117 lb.
<b>Cord Length</b>	33 ft.

Please note that specifications are subject to change without notice

**Use only recommended tools & accessories**



4D-35LEX Suspended Powerhead



4D-35LEX DT MFS HEPA with Recovery Tank removed



4D-35LEX DT with optional Front Mounted Floor Brush (MFS version shown)



Ø2" (Ø50 mm) Static Dissipative Tools and Accessories (Bulk Wand) - Included



HEPA Filter - Included



Main Cloth Filter and Cage, Static Dissipative - Included



Conductive Polyliner Recovery Bag - Included



Optional Front Mount Floor Tool