Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243

Complies with NFPA 77 "Recommended Practice on Static Electricity"

Dual Motor | DRY REC - Dry Recovery | SD Accessories - Included

Specifications For 4D-200L (DA) 4W HEPA ORDLOC-652

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
4D-200L (DA) 4W HEPA ORDLOC-652	112118A-652	120 V	60 Hz	Single	2040 W	2.7 HP	15.2 A	200 CFM	90 " H_2O	20 Amps	55 Gal

Please note that specifications are subject to change without notice

Technical Sheet For   4D-200L (DA) 4W HEPA ORDLOC-652

FILTERS - Included	
Part #	**Description**
215373A-01	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, ASSEMBLED WITH PLATE AND NO U-CHANNEL GASKET
215974	SD* PRE-FILTER w/CLAMP FOR HEPA FILTER #215373, MADE OF CONDUCTIVE EPITROPIC POLYESTER FELT w/PTFE
218425AT	MAIN FILTER ASMBLY SD* PTFE LAMINATED, w/FILTER SUPPORT RING & CAGE, FOR MODEL 4D-200L EX (DA)

DRUM ADAPTOR - Included	
Part #	**Description**
217266	DRUM ADAPTOR ASSEMBY w/2.5" SUCTION INLET,POWDER COATED, WITH LATCHES AND GASKET FOR 4D-200 LEX

55 GALLON DRUM ASSEMBLY - Included	
Part #	**Description**
211342B	55 GALLON DRUM ASSEMBLY WITH (3) LATCHES, NO INTAKE, POWDER COATED

4-WHEEL CART ASSEMBLY - Included	
Part #	**Description**
212423	4 WHEEL CART ASSEMBLY -POWDER COATED (55 GALLON)

TOOLS AND ACCESSORIES - Optional	
Part #	**Description**
500540	CRUSHPROOF SUCTION HOSE ASMBLY 2"(50mm) x15'(4.5m) STATIC CONDUCTIVE w/2"(50mm) FEMALE CAMLOCK (ALUM
500160	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), ALUMINUM, WITH TAPER FOR FLOOR TOOL
500161A	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE
500156B	CREVICE TOOL SD* (NO COUPLING) Ø2"(50mm)x15"(38cm) -ALUMINUM
501187AM	DUSTING BRUSH, 2"(50mm) OD x 4"(10cm), CONDUCTIVE RUBBER WITH CONDUCTIVE BRISTLES