



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243



Complies with NFPA 77 "Recommended Practice on Static Electricity"

### Characteristics



Stainless  
General



SD Accessories  
- Included



HEPA -  
Included



High Filtration  
Efficiency Unit



Dry Recovery



Brushless Motor  
Available



- Ideal for housekeeping and general cleaning
- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- Protected against ingress of dust
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- For dry recovery only
- Manual Filter Shaker (MFS) system
- Stainless steel tank Type 430 fits any application
- Filter blockage indicator light
- Includes a complete static dissipative tool kit

## Specifications

2D-25L (DT) MFS HEPA ORDLOC-652	111405A
<b>Model Name</b>	2D-25L (DT) MFS HEPA ORDLOC-652
<b>Type (Powerhead)</b>	Electric
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	1200 W
<b>Power</b>	1.6 HP
<b>Amperage</b>	10.5 A
<b>Air Flow</b>	110 CFM
<b>Vacuum Pressure</b>	107 " H <sub>2</sub> O
<b>Sound Level</b>	75 dB(A)
<b>Type of Power Outlet</b>	120V
<b>Suction Inlet Port</b>	60 mm
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)
<b>Dust Recovery Tank</b>	6.6 Gal
<b>Cord Length</b>	35 ft.

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



Longer Life Brushless Motor Available (always with 2 x H14 HEPA filters)