



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243



Complies with NFPA 77 "Recommended Practice on Static Electricity"

Characteristics



Stainless
General



SD Tools &
Accessories



HEPA -
Included



High Filtration
Efficiency Unit



Dry Recovery



Dual Motor



- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- Protected against ingress of dust
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Includes a complete static dissipative tool kit
- Brushless motor available

Specifications

4D-55L (DT) MFS HEPA ORDLOC-652	112111A
Model Name	4D-55L (DT) MFS HEPA ORDLOC-652
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	2040 W
Power	2.7 HP
Amperage	15.2 A
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ O
Type of Power Outlet	20 Amps
Suction Inlet Port	2 "
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	14.5 Gal
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories