

CLEANING MACHINES FOR UNCLASSIFIED (GENERAL PURPOSE) AREAS All the electrical components are certified by an NBTL such as

All the electrical components are certified by an NRTL such as UL, CSA or $\ensuremath{\mathsf{ETL}}$



Complies with NFPA 77 "Recommended Practice on Static Electricity"



Efficiency Unit







Detachable Tank



- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- Industrial continuous duty vacuum system
- Very powerful machine capable of working with large diameter suction hoses up to 70 mm. Perfect for Food industry, machine shops, Plastics industry, Ceramics industry, printing, textiles, heavy clean-up, etc.
- Regenerative blower with TEFC induction motor rated for continuous duty
- Includes a star shaped main filter
- Manual Filter Shaker (MFS) system
- Upstream filter cartridge for fine dust
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Filter chamber and recovery tank made of stainless steel Type 304
- Sight glass installed on recovery tank
- Includes a complete static dissipative tool kit



Specifications

TV-730 (DT) MFS HEPA ORDLOC- 652	111214A1-652	111214A5-652
Model Name	TV-730 (DT) MFS HEPA ORDLOC-652	TV-730 (DT) MFS HEPA ORDLOC-652
Type (Powerhead)	Electric	Electric
TEFC Motor	Yes	Yes
Tension	460 V	575 V
Frequency	60 Hz	60 Hz
Phase	Three	Three
Wattage	3450 W	3450 W
Power	4.6 HP	4.6 HP
Amperage	7.3 A	5.8 A
Air Flow	185 CFM	185 CFM
Vacuum Pressure	104 " H ₂ 0	104 " H ₂ 0
Type of Power Outlet	Not Included	Not Included
Suction Inlet Port	70 mm	70 mm
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Filter Type	Star Shaped + Cartridge	Star Shaped + Cartridge
Filter Surface Area	21 ft² + 10.8 ft²	21 ft² + 10.8 ft²
Dust Recovery Tank	15.6 Gal	15.6 Gal
Length	43 "	43 "
Width	24.5 "	24.5 "
Height	50 "	50 "
Weight (Vacuum Only)	303 lb.	303 lb.
Cord Length	30 ft.	30 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories




Filter Blockage Indicator Gage. Manual Starter with Overload Protection



Side Mounted Manual Filter Shaker



Sight Glass on Recovery Tank



Integrated Silencer



Side Mounted Manual Filter Shaker (Internal View)



HEPA Filter - Included



Conductive Star Shaped Filter with Cage for ORDLOC 652 - Included



Tangential Suction Inlet, 70 mm, Aluminum



Ø2" (Ø50 mm) Static Conductive Tool Kit - Included