



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243



Complies with NFPA 77 "Recommended Practice on Static Electricity"

Characteristics



Stainless
General



SD Accessories
- Included



HEPA -
Included



High Filtration
Efficiency Unit



Dry Recovery



Brushless Motor
Available



- Ideal for housekeeping and general cleaning
- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- Protected against ingress of dust
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Heavy duty 2-stage by-pass motor
- Longer life brushless motor available. Always with 2 x H14 HEPA filters
- For dry recovery only
- Manual Filter Shaker (MFS) system
- Stainless steel tank Type 430 fits any application
- Filter blockage indicator light
- Includes a complete static dissipative tool kit

Specifications

2D-25L (DT) MFS HEPA ORDLOC-652	111405A
Model Name	2D-25L (DT) MFS HEPA ORDLOC-652
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	1200 W
Power	1.6 HP
Amperage	10.5 A
Air Flow	110 CFM
Vacuum Pressure	107 " H ₂ O
Sound Level	75 dB(A)
Type of Power Outlet	120V
Suction Inlet Port	60 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	6.6 Gal
Cord Length	35 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Longer Life Brushless Motor Available (always with 2 x H14 HEPA filters)