



Complies with NFPA 77 "Recommended Practice on Static Electricity"



Applicable requirements :  
Standard(s) for Electric Vacuum Cleaning Machines and Blower Cleaners (UL-1017)

### Characteristics



Three Motors



HEPA -  
Included



High Filtration  
Efficiency Unit



Dry Recovery



Detachable  
Tank



SS 304



SD Accessories  
- Included



- Complies with NFPA 652 paragraph 8.4.2.2.1.7 and NFPA 654 paragraph 8.4.3.7 (1) to (7)
- 3 motors (individual). 1, 2 or 3 motors can be used at one time
- Includes a star shaped main filter
- Manual Filter Shaker (MFS) system
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Filter chamber and recovery tank made of stainless steel Type 304
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Pressure gauge and illuminated filter blockage indicator
- Includes a complete static dissipative tool kit

## Specifications

TV-201 (DT) MFS HEPA ORDLOC-652	111887A-652
<b>Model Name</b>	TV-201 (DT) MFS HEPA ORDLOC-652
<b>Type (Powerhead)</b>	Electric
<b>Tension</b>	120 V
<b>Frequency</b>	60 Hz
<b>Phase</b>	Single
<b>Wattage</b>	2400 W
<b>Power</b>	3.2 HP
<b>Amperage</b>	15.8 A
<b>Air Flow</b>	270 CFM
<b>Vacuum Pressure</b>	71.5 " H <sub>2</sub> O
<b>Sound Level</b>	70 dB(A)
<b>Type of Power Outlet</b>	20 Amps
<b>Suction Inlet Port</b>	70 mm
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)
<b>Filter Type</b>	Star Shaped + HEPA
<b>Filter Surface Area</b>	21 ft <sup>2</sup> + 10.8 ft <sup>2</sup>
<b>Dust Recovery Tank</b>	10.5 gal. (40 L)
<b>Length</b>	29 "
<b>Width</b>	25 "
<b>Height</b>	44 "
<b>Weight (Vacuum Only)</b>	122 lb.
<b>Cord Length</b>	30 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



Side Mounted Manual Filter Shaker



Tangential Suction Inlet, 70 mm, Aluminum



HEPA Filter Cartridge - Included



Conductive Star Shaped Filter with Cage for ORDLOC 652 - Included



Optional Front Mount Floor Tool



Detachable Recovery Tank for easy emptying



Ø2" (Ø50 mm) Static Conductive Tool Kit - Included



Independent Control for each motor. Pressure Gage and Filter Blockage Indicator