U.S. Headquarters

Tiger-Vac Inc.
11 SW 12th Ave #112
Dania, FL 33004
USA

Tel: 1-800-668-4437 (954-925-3625)
Fax: 1-800-668-4439 (954-925-3626)
Website: http://www.tiger-vac.com
Email: sales@tiger-vac.com

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: http://www.tiger-vac.com
Email: sales@tiger-vac.com

CLEANING MACHINES FOR
UNCLASSIFIED (GENERAL PURPOSE)
AREAS
All the electrical components are certified by
an NRTL such as UL, CSA or ETL

Pharma Applications | Dry Recovery | Cleanroom Compatible | ULPA - Optional | HEPA - Optional | Continuous Duty

Specifications For CD-1501 CR (STD) SERIES

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank	Dry Recovery - Disposable Filter Bag
CD-1501 CR (STD) - P/C & S/S	110984A1	460 V	60 Hz	Three	1900 W	2.5 HP	4 A	148 CFM	140 " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 64 dB(A)											
CD-1501 CR (STD) - P/C & S/S	110984A2	230 V	60 Hz	Three	1900 W	2.5 HP	7 A	148 CFM	140 " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 64 dB(A)											
CD-1501 CR (STD) - P/C & S/S	110984A3	120 V	60 Hz	Single	1500 W	2 HP	18 A	120 CFM	111+ " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 69 dB(A)											
CD-1501 CR (STD) - P/C & S/S	110984A4	230 V	60 Hz	Single	1500 W	2 HP	9 A	120 CFM	111+ " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 69 dB(A)											
CD-1501 CR (STD) - STAINLESS STEEL	110986A1	460 V	60 Hz	Three	1900 W	2.5 HP	4 A	148 CFM	140 " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 64 dB(A)											
CD-1501 CR (STD) - STAINLESS STEEL	110986A2	230 V	60 Hz	Three	1900 W	2.5 HP	7 A	148 CFM	140 " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 64 dB(A)											
CD-1501 CR (STD) - STAINLESS STEEL	110986A3	120 V	60 Hz	Single	1500 W	2 HP	18 A	120 CFM	111+ " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 69 dB(A)											
CD-1501 CR (STD) - STAINLESS STEEL	110986A4	230 V	60 Hz	Single	1500 W	2 HP	9 A	120 CFM	111+ " H_2O	Not Included	7.5 Gal	4 gal.
	Dimensions: H43" x W19.5" x L13.5" Weight: 113.5 lb. Sound Level: 69 dB(A)											

Please note that specifications are subject to change without notice

Technical Sheet For   CD-1501 CR (STD) SERIES

HEPA FILTER AND ACCESSORIES - INTERNAL - UPSTREAM - Optional

Part #	Description
212304B	HEPA FILTER (H14)

ULPA FILTER AND ACCESSORIES - EXHAUST - DOWNSTREAM - Optional

Part #	Description
211027	ULPA FILTER (U15)
215158	DOWNSTREAM HOUSING ASSEMBLY (STAINLESS STEEL AISI 304)W/ULPA FILTER #211027 2"(50mm)x24"(61cm)NIPPLE
215160	DOWNSTREAM HOUSING ASSEMBLY (POWDER COATED)W/ULPA FILTER #211027 2"(50mm)x24"(61cm)NIPPLE

EXHAUST SILENCER - Included

Part #	Description
215360	MUFFLER, PVC, WHITE

EXHAUST FILTRATION - Optional

Part #	Description
212496A	EXTERNAL HEPA HOUSING ASSEMBLY WITH GASKET, Ø2"(50mm)CAMLOCK VENTING EXHAUST -SS ELECTROPOLISHED
212497	ADAPTOR PLATE FOR EXTERNAL HEPA HOUSING 212496 -STAINLESS STEEL
213035	ADAPTOR PLATE WITH Ø2"(50mm) CAMLOCK VENTING EXHAUST -STAINLESS STEEL

FILTERS AND ACCESSORIES - Included

Part #	Description
213390AT	MAIN FILTER ASSEMBLY WITH LACES (NO CAGE)(PRE-FILTER NO LONGER REQUIRED)
213386A	FILTER CAGE, STAINLESS STEEL, ELECTROPOLISHED

Ø1.25" (Ø32mm) TOOLS AND ACCESSORIES - Optional

Part #	Description
323540	VACUFLEX SUCTION HOSE ASSEMBLY FOR EMI-CWR SS 1.25"(32mm)x10' SD* W/FEMALE CAMLOCK&STRAIGHT HANDLE
323540B	VACUFLEX SUCTION HOSE ASSEMBLY 1.25"x10' SD* w/ 2" (50MM) FEMALE CAMLOCK & STRAIGHT HANDLE S/S
323331	STAINLESS STEEL WANDS 1.25" 32cm (SET OF 2) - ONE CURVED AND ONE STRAIGHT
323311A	COMBI TOOL 1.25"(32mm) x 11"(28cm), STATIC CONDUCTIVE PLASTIC WITH CONDUCTIVE NYLON BRISTLES
323317A	UTILITY FLOOR TOOL, 1.25"(Ø32mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/GREY SQUEEGEE BLADES
323312A	ROUND BRUSH, 1.25"(32mm) x 3"(7.5cm), ESD SAFE PLASTIC, WITH HOLE FOR BUTTON LOCK
323314A	UPHOLSTERY FLAT TOOL, 1.25"(32mm) x 5"(13cm), ESD SAFE PLASTIC
323313A	CREVICE TOOL, 1.25"(32mm) x 8"(20cm), BLACK, ESD SAFE PLASTIC w/HOLE FOR BUTTON LOCK
323316	MICRO TOOL KIT, Ø1.25"(32mm), ESD* SAFE PLASTIC
323321A	ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm), ESD SAFE PLASTIC
211065	GROUND CONTINUITY TESTER

Ø1.5" (Ø38mm) TOOLS AND ACCESSORIES - Optional

Part #	Description
381427	CLEAR URETHANE SUCTION HOSE ASMBLY SD* 1.5"(38mm) x 12.5'(3.8m) w/SS FEMALE CAMLOCK &SS FEMALE SCREW
381427B	CLEAR URETHANE SUCTION HOSE ASMBLY 1.5" x 12.5', w/ 2" SS FEMALE CAMLOCK & 1.5" SS FEMALE SCREW TYPE
381366	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5"(38mm) x 54"(137cm), STAINLESS STEEL w/STAINLESS TOOL COUPLING
381370	FLOOR TOOL ASSEMBLY, AUTOCLAVABLE, 1.5"(38mm) x 14"(36cm), STAINLESS STEEL w/WHITE NITRILE BLADES
381372	CREVICE TOOL Ø1.5"(38mm)x11"(27.9cm) -STAINLESS STEEL

DUAL INTAKE INSTALLATION KIT AND ACCESSORIES - Optional

Part #	Description
501525	INTAKE INSTALLATION KIT 2" (50MM) FOR Y CONNECTOR AND DUST EXTRACTION ARM ASSEMBLIES
501500	WYE CONNECTOR 2" FEMALE CAMLOCK WITH TWO 1.5"(38mm) MALE CAMLOCK, STAINLESS STEEL
501504	WYE CONNECTOR, 2" FEMALE CAMLOCK ALUMINUM x (2) 1.5" HOSE BARB, ASSEMBLY WITH ONE PLUG

DUST EXTRACTION ARM - Optional

Part #	Description
218037	DUST EXTRACTION ARM, DIAM: 3"(75mm) x REACH: 5'(1.5m), STAINLESS STEEL
218038	DUST EXTRACTION ARM, DIAM: 3"(75mm) REACH: 5'(1.5m), WHITE