

### U.S. Headquarters

Tiger-Vac Inc.  
11 SW 12th Ave #112  
Dania, FL 33004  
USA

Tel: 1-800-668-4437 (954-925-3625)  
Fax: 1-800-668-4439 (954-925-3626)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)

### International Headquarters

Tiger-Vac International Inc.  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



CLEANING MACHINES FOR  
UNCLASSIFIED (GENERAL PURPOSE)  
AREAS  
All the electrical components are certified by  
an NRTL such as UL, CSA or ETL



Continuous Duty



Detachable Tank



Dry Recovery



HEPA Filter Available  
HEPA - Optional



ULPA Filter Available  
ULPA - Optional



Pharma Applications



Cleanroom Compatible

## Specifications For CD-2600 CR (MRP) SERIES

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
CD-2600 CR (MRP) - P/C & S/S	111452A1	460 V	60 Hz	Three	1900 W	2.5 HP	4 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111452A2	230 V	60 Hz	Three	1900 W	2.5 HP	7 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111452A4	230 V	60 Hz	Single	1900 W	2.5 HP	7.2 A	140 CFM	111+ " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111452A5	575 V	60 Hz	Three	1900 W	2.5 HP	2.6 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111453A1	460 V	60 Hz	Three	2600 W	3.5 HP	4.7 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L34"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111453A2	230 V	60 Hz	Three	2600 W	3.5 HP	9.4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L34"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - P/C & S/S	111453A5	575 V	60 Hz	Three	2600 W	3.5 HP	4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L34"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - STAINLESS STEEL	111456A1	460 V	60 Hz	Three	1900 W	2.5 HP	4 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - STAINLESS STEEL	111456A2	230 V	60 Hz	Three	1900 W	2.5 HP	7 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						
CD-2600 CR (MRP) - STAINLESS STEEL	111456A4	230 V	60 Hz	Single	1900 W	2.5 HP	7.2 A	140 CFM	111+ " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"		Weight: 247 lb.		Sound Level: 68 dB(A)						

<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111456A5</b>	575 V	60 Hz	Three	1900 W	2.5 HP	2.6 A	148 CFM	140 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										
<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111457A1</b>	460 V	60 Hz	Three	2600 W	3.5 HP	4.7 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										
<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111457A2</b>	230 V	60 Hz	Three	2600 W	3.5 HP	9.4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										
<b>CD-2600 CR (MRP) - STAINLESS STEEL</b>	<b>111457A5</b>	575 V	60 Hz	Three	2600 W	3.5 HP	4 A	219 CFM	145 " H <sub>2</sub> O	Not Included	9.5 Gal
	Dimensions: H75" x W20" x L26"      Weight: 247 lb.      Sound Level: 68 dB(A)										

Please note that specifications are subject to change without notice

## Technical Sheet For **CD-2600 CR (MRP) SERIES**

### HEPA/ULPA FILTERS AND ACCESSORIES - Optional

Part #	Description
213182	HEPA FILTER , 13.8125" x 3.875" HIGH, MINIMUM EFFICIENCY 99.995% ON 0.3 MICRON, w/GASKET INSTALLED
213181	ULPA FILTER (U15), Ø13.8125" x 3.875"(35.1cm X 98.4mm) HIGH, RATED 250 CFM
215014B	HEPA HOUSING FOR CD-2600-STD, CRS -POWDER COATED
215012	HEPA HOUSING FOR CD-2600 -STAINLESS STEEL 304

### REVERSE PURGE FILTER CARTRIDGE - Included

Part #	Description
214182A	FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD,1" PLEATS, 13 SQ.FT

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
214987	POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

### TOOLS AND ACCESSORIES - Optional

Part #	Description
500390	CLEAR URETHANE SUCTION HOSE SD* Ø2"(50mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT)
635078	CLEAR URETHANE SUCTION HOSE SD* Ø2.5"(64mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT)
500159	CLAMP, TRIDON (SCREW TYPE) SIZE 32 -STAINLESS STEEL
635016	HOSE CLAMP -STAINLESS STEEL SCREW TYPE FOR Ø2.5"(64mm)HOSE
500198	HOSE CUFF EXPANDER FOR Ø2"(50mm)VACUFLEX HOSE TO Ø2.5"(63.5mm)ADAPTOR (500168+635248)
500168	HOSE CUFF Ø2"(50mm) FOR Ø2"(50mm) VACUFLEX HOSE
635248	HOSE CUFF FOR Ø2.5"(64mm) WIRE SUPPORTED HOSE