



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243

## Characteristics



Pharma Applications



Cleanroom Compatible



Wet and Dry Recovery



ULPA - Included




High Filtration Efficiency Unit



Activated Carbon



Accessories Included



EMI Shielded



- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- EMI/RFI Shielded
- 5-stage filtration system, includes dual ULPA filters (U15) (one for the working air and one for the cooling air), double cloth filter, and disposable filter bags
- Available with a Middle Ring with Activated Carbon (MRAC) for the adsorption of toxic/noxious fumes and vapors
- Designed for use in contamination controlled environments
- Heavy duty 2-stage by-pass motor
- For wet & dry recovery
- Polyethylene recovery tank with polished metal powerhead
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.

## Specifications

CWR POLY SERIES	110498A	110499A
<b>Model Name</b>	CWR-15 (4W) POLY	CWR-8 POLY
<b>Type (Powerhead)</b>	Electric	Electric
<b>Tension</b>	120 V	120 V
<b>Frequency</b>	60 Hz	60 Hz
<b>Phase</b>	Single	Single
<b>Wattage</b>	1200 W	1050 W
<b>Power</b>	1.6 HP	1.6 HP
<b>Amperage</b>	10.5 A	10.5 A
<b>Air Flow</b>	110 CFM	110 CFM
<b>Vacuum Pressure</b>	107 " H <sub>2</sub> O	107 " H <sub>2</sub> O
<b>Sound Level</b>	75 dB(A)	75 dB(A)
<b>Type of Power Outlet</b>	120V	120V
<b>Suction Inlet Port</b>	1.5 "	1.5 "
<b>Cart Type</b>	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
<b>Filter Cleaning</b>	None	None
<b>Dust Recovery Tank</b>	12.5 gal.	6.5 Gal
<b>Dry Recovery - Disposable Filter Bag</b>	5 gal.	2.5 gal.
<b>Liquid Recovery Capacity</b>	12.5 gal.	6.5 gal.
<b>Length</b>	"	23 "
<b>Width</b>	"	19 "
<b>Height</b>	"	30 "
<b>Weight (Vacuum Only)</b>	lb.	40 lb.
<b>Cord Length</b>	35 ft.	35 ft.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories




CWR-8 Poly Tank



ULPA Filter - Included



CWR Tools and Accessories - Included



CWR Tools and Accessories - Optional



Needle Trap - Optional