

## The name to vacuum with

Designed for use in:

Division 1, Class I, Groups A, B, C and D Division 1, Class II, Groups E, F, G

Hazardous Locations as defined in the National Electrical Code (NFPA 70)

C€ (E) II 2D

Ex h IIIC T85°C Db

For use in ATEX Zone 21 & Zone 22 (Dust) potentially explosive atmospheres

**ATEX** 

Ex h IIC T6 Gb Ex h IIIC T85°C Db IECEx LCIE 17.0076 X



**GUARANTEED** for the Safe Recovery of Combustible/Conductive **Dusts and Flammable Liquids** 

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Complies with NFPA 77 "Recommended Practice on Static Electricity"



## **Characteristics**





ohms









HEPA - Optiona

Filter Element

- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- Coalescing Filter Element (CFE) for moisture removal
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Pneumatic (air-operated)
- Fuel, oil and solvent recovery. Ideal for the recovery of hydrazine
- Designed for the adsorption of toxic/noxious vapors, fumes and odors
- stainless steel Type 304 interceptor tank
- Equipped with a heavy duty powder coated hydraulic cart for easy emptying of recovered material. Cart has static dissipative or conductive wheels

## **Specifications**

SS-55 HRS TE (HY-C)	110415
Model Name	SS-55 HRS TE (HY-C)
Type (Powerhead)	Pneumatic
Venturi	Single
Venturi (diam.)	6 mm
Minimum Compressor	15 HP
Air Line Size (Diam.)	1/2 "
Input Air Volume	45 CFM
Input Air Pressure	80 PSI
Air Flow	120 CFM
Vacuum Pressure	180 " H <sub>2</sub> 0
Suction Inlet Port	2 "
Cart Type	Hydro Cart (HYC)
Filter Cleaning	None
Dust Recovery Tank	40 Gal
Liquid Recovery Capacity	45 gal.

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



Main Cloth Filter, Static Dissipative - Included



Stainless Steel Mesh Filter - Included



Nitrile Suction Hose - Included



Strainer Basket for TE Series - Included

Tel: 1-800-668-4437 (954-925-3625) Fax: 1-800-668-4439 (954-925-3626) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com