

Characteristics



EX Certified




Dry Recovery



Continuous Duty



Stainless General



HEPA-Included



High Filtration Efficiency Unit



- Designed to capture airborne dust
- The first stage of filtration is an aluminized spun bond cartridge. Filtration efficiency of 97% at 0.3 micron
- Downstream HEPA filter with an efficiency of 99.99% at 0.3 micron - included. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility
- Low pressure, high flow rate
- Filter cartridge pulse cleaning by compressed air
- Heavy duty stainless steel Type 304 construction
- Heavy duty wheels and swivel castors. 2 wheels equipped with brakes. All 4 wheels are conductive
- Handles for ease of movement
- Easy access to filters
- Low center of gravity to prevent tipping
- Continuous duty single phase or 3-phase (TEFC) explosion proof/dust ignition proof motor
- Thermal overload for motor
- Optional dust extraction arm available - Ø6" (150 mm)

Specifications

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Purge Filter Cartridge - Included



CD-600 EX SS Control panel



CD-600 SS Housing side door with access to Cartridge



CD-600/TV-600 SS Purge Filter Cartridge in housing



Optional Differential Pressure Gauge for SS Models (Filter Blockage Indicator) available



Wall Mount Bracket for Dust Extraction Arm - Optional