



Applicable Requirements : ANSI/UL 1017 CSA C22.2 No.243



Characteristics











- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Designed for general cleaning in the Food industry
- Heavy duty 2-stage by-pass motor
- Manual Reverse Purge (MRP) with static dissipative reverse purge cartridge
- For dry recovery only
- Heavy duty powder coated body and stainless steel recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels
- Includes a complete tool kit with a clear suction hose. A variety of optional accessories are available including autoclavable and ESD safe hoses and tools

Specifications

2D-25L (DT) MRP WT SERIES	111411A	111413A
Model Name	2D-25L (DT) MRP WT NO HEPA	2D-25L (DT) MRP WT HEPA
Type (Powerhead)	Electric	Electric
Tension	120 V	120 V
Frequency	60 Hz	60 Hz
Phase	Single	Single
Wattage	1200 W	1200 W
Power	1.6 HP	1.6 HP
Amperage	10.5 A	10.5 A
Air Flow	110 CFM	110 CFM
Vacuum Pressure	107 " H ₂ 0	107 " H ₂ 0
Sound Level	75 dB(A)	75 dB(A)
Type of Power Outlet	120V	120V
Suction Inlet Port	2 "	2 "
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Reverse Purge (MRP)	Manual Reverse Purge (MRP)
Dust Recovery Tank	6.5 Gal	6.5 Gal
Length	23 "	23 "
Width	21 "	21 "
Height	40 "	40 "
Weight (Vacuum Only)	50 lb.	50 lb.
Cord Length	35 ft.	35 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Conductive Aluminized Spun Bond Reverse Purge Cartridge (shown with and without optional skirt) - Included



Clear Polyliner Recovery Bags - Included



Ø1.5" (Ø38 mm) Tools and Accessories - Included



25L Detachable Tank