



Applicable Requirements :  
ANSI/UL 1017  
CSA C22.2 No.243

## Characteristics



HEPA -  
Included



High Filtration  
Efficiency Unit



Detachable  
Tank



Dry Recovery



Dual Motor



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels

## Specifications

4D-25L (DT) MFS HEPA	111415A
Model Name	4D-25L (DT) MFS HEPA
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	2040 W
Power	2.7 HP
Amperage	15.2 A
Air Flow	200 CFM
Vacuum Pressure	90 " H <sub>2</sub> O
Sound Level	78 dB(A)
Type of Power Outlet	Not Included
Suction Inlet Port	2 "
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	6.5 Gal
Length	24 "
Width	25 "
Height	42 "
Weight (Vacuum Only)	86 lb.
Cord Length	33 ft.

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38 mm) Static Dissipative Tools and Accessories - Optional