



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243

Characteristics



HEPA -
Included



High Filtration
Efficiency Unit



Detachable
Tank



Dry Recovery



Dual Motor



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Reverse Purge (MRP) with static dissipative reverse purge cartridge
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels

Specifications

4D-25L (DT) MRP HEPA	111931A
Model Name	4D-25L (DT) MRP HEPA
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	2040 W
Power	2.7 HP
Amperage	15.2 A
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ O
Sound Level	78 dB(A)
Type of Power Outlet	Not Included
Suction Inlet Port	2 "
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Reverse Purge (MRP)
Dust Recovery Tank	6.6 Gal
Length	23 "
Width	21 "
Height	39.5 "
Weight (Vacuum Only)	74 lb.
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Conductive Aluminized Spun Bond Reverse Purge Cartridge
(shown with and without optional skirt) - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38 mm) Static Dissipative Tools and Accessories -
Optional