

U.S. Headquarters

Tiger-Vac Inc.
11 SW 12th Ave #112
Dania, FL 33004
USA

Tel: 1-800-668-4437 (954-925-3625)
Fax: 1-800-668-4439 (954-925-3626)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243



HEPA -
Included



High Filtration
Efficiency Unit



Detachable
Tank



Dry Recovery



Dual Motor

Specifications For 4D-25L (DT) MRP HEPA

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank
4D-25L (DT) MRP HEPA	111931A	120 V	60 Hz	Single	2040 W	2.7 HP	15.2 A	200 CFM	90 " H ₂ O	Not Included	6.6 Gal
Dimensions: H39.5" x W21" x L23" Weight: 74 lb. Sound Level: 78 dB(A)											

Please note that specifications are subject to change without notice

Technical Sheet For 4D-25L (DT) MRP HEPA

HEPA FILTER AND ACCESSORIES - Included

Part #	Description
215983	HEPA FILTER (MID HEIGHT), 6.375" x 7.40" HIGH w/GASKET, 99.995% EFFICIENCY ON 0.3 MICRON (H14)

REVERSE PURGE FILTER CARTRIDGE - Included

Part #	Description
214182A	FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD, 1" PLEATS, 13 SQ.FT

FILTERS AND ACCESSORIES - Optional

Part #	Description
218095	POLYESTER SAFETY FILTER ASSEMBLY w/CLAMP FOR 4D (FITS AROUND HEPA HOUSING #218093B)

POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
214987	POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

TOOLS AND ACCESSORIES - Optional

Part #	Description
383438-50	CRUSHPROOF SUCTION HOSE, BLACK STATIC CONDUCTIVE (NO WIRE), Ø1.5" (Ø38mm) x 50'
383434	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383436	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383435	EXPANDER HOSE CUFF, 1.5"(38mm) HOSE TO 2"(50mm) TUBE, STATIC CONDUCTIVE, BLACK
500175	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING

