



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243

Characteristics



HEPA -
Included



High Filtration
Efficiency Unit



Dual Motor



Wet and Dry
Recovery



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- For wet & dry recovery
- Heavy duty powder coated steel construction
- Silent operation
- Mounted on a Tilting Cart (TC) for easy disposal of recovered materials

Specifications

4D-57 (TC) RE HEPA	110942A
Model Name	4D-57 (B) (TC) RE HEPA
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	1955 W
Power	2.6 HP
Amperage	17 A
Air Flow	200 CFM
Vacuum Pressure	90 " H ₂ O
Sound Level	69 dB(A)
Type of Power Outlet	Not Included
Suction Inlet Port	2 "
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Dust Recovery Tank	55 Gal
Liquid Recovery Capacity	55 gal.
Width	28 "
Height	51 "
Weight (Vacuum Only)	135 lb.
Cord Length	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Main Cloth Filter - Included



Liquid Filter - Included



PVC Crushproof Suction Hose Assembly - Included



Tools and Accessories (Toolkit 5) - Optional