



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243

Characteristics



HEPA Filter Available

HEPA - Optional



Detachable Tank



Dry Recovery



Dual Motor



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- For general housekeeping
- Dual bypass/dual speed heavy duty motors. 2000W (2400 max.)
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels

Specifications

4D-55L (DT) HD MFS SERIES	112109A	112110A
Model Name	4D-55L (DT) HD MFS NO HEPA	4D-55L (DT) HD MFS HEPA
Type (Powerhead)	Electric	Electric
Tension	120 V	120 V
Frequency	60 Hz	60 Hz
Phase	Single	Single
Wattage	2040 W	2040 W
Power	2.7 HP	2.7 HP
Amperage	15.2 A	15.2 A
Air Flow	200 CFM	200 CFM
Vacuum Pressure	90 " H ₂ O	90 " H ₂ O
Sound Level	78 dB(A)	78 dB(A)
Type of Power Outlet	Not Included	Not Included
Suction Inlet Port	2 "	2 "
Cart Type	Detachable Tank (DT)	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)	Manual Filter Shaker (MFS)
Dust Recovery Tank	14.5 Gal	14.5 Gal
Length	23 "	23 "
Width	21 "	21 "
Height	55 "	55 "
Weight (Vacuum Only)	91 lb.	91 lb.
Cord Length	33 ft.	33 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



55L Detachable Recovery Tank



HEPA Filter - Included



Ø1.5" (Ø38 mm) Static Dissipative Tools and Accessories - Optional



Ø2" (Ø50 mm) Static Dissipative Tools and Accessories - Optional



Clear Polyliner Recovery Bags - Optional