



Applicable Requirements :
ANSI/UL 1017
CSA C22.2 No.243

Characteristics



Static
Dissipating



HEPA -
Included



Detachable
Tank



Dry Recovery



SS 430



High Filtration
Efficiency Unit



- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- For general housekeeping
- Heavy duty 2-stage by-pass motor
- Manual Filter Shaker (MFS) system
- For dry recovery only
- Stainless steel Type 430 body and recovery tank
- Detachable recovery tank (DT) for easy disposal of recovered materials
- Equipped with a 4-wheel cart and tool basket. Cart has static dissipative or conductive wheels

Specifications

2D-25L (DT) MFS HEPA	111402A
Model Name	2D-25L (DT) MFS HEPA
Type (Powerhead)	Electric
Tension	120 V
Frequency	60 Hz
Phase	Single
Wattage	1200 W
Power	1.6 HP
Amperage	10.5 A
Air Flow	110 CFM
Vacuum Pressure	107 " H ₂ O
Sound Level	75 dB(A)
Type of Power Outlet	120V
Suction Inlet Port	2 "
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dust Recovery Tank	6.5 Gal
Length	23 "
Width	21 "
Height	39.5 "
Weight (Vacuum Only)	50 lb.
Cord Length	35 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Main Cloth Filter - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38 mm) Static Dissipative Tools and Accessories -
Optional