

Characteristics




Cleanroom
Compatible



Pharma
Applications



Hydrocart



Activated
Carbon



Wet Recovery



Accessories
Included



Corrosive
Recovery



Wear Protective
Clothing (PPE)



- Designed for the recovery of acids and corrosive liquids
- Pneumatic (air-operated)
- Available with a variety of activated carbon, including KINA 3® activated carbon for the adsorption of chloride and acid vapors (HF, HCL, etc). Other types of activated carbon are available. Carbon cartridges must be ordered separately - not included
- For liquid recovery
- Acid-resistant polyethylene, nylon and PVC
- Available with a 4-wheel dolly, tilting cart, or hydro-cart
- 4-wheel dolly, and tilting cart available in stainless steel
- Includes a complete tool kit.

Specifications

CS-ARU-15 STD SERIES	111433	111435
Model Name	CS-ARU-15 (TC)	CS-ARU-15 STD (HY-C)
Type (Powerhead)	Pneumatic	Pneumatic
Venturi	Single	Single
Venturi (diam.)	6 mm	6 mm
Minimum Compressor	15 HP	15 HP
Air Line Size (Diam.)	1/2 "	1/2 "
Input Air Volume	45 CFM	45 CFM
Input Air Pressure	80 PSI	80 PSI
Air Flow	110 CFM	110 CFM
Vacuum Pressure	170 " H ₂ O	170 " H ₂ O
Suction Inlet Port	1.5 "	1.5 "
Cart Type	Tilt Cart (TC)	Hydro Cart (HYC)
Filter Cleaning	None	None
Liquid Recovery Capacity	12.5 gal.	12.5 gal.
Length	"	52 "
Width	"	21 "
Height	"	55 "
Weight (Vacuum Only)	lb.	230 lb.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



ARU STD Tools and Accessories - Included



Liquid Filter - Included



Activated Carbon Cartridge - Optional



CS-ARU-15 STD (HY-C)