

Designed for use in :

Division 2, Class II, Groups F and G Hazardous Locations as defined in the National Electrical Code

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

NFPA77 Complies with N

Complies with NFPA 77 "Recommended Practice on Static Electricity"

Tige-Vac

Characteristics













Dissipating

HEPA -Included

High Filtration Efficiency Unit

Genera

SD Accessories - Included

Wet and Dr Recovery

- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility included
- For general housekeeping
- Designed for the recovery of designated substances/hazardous dusts such as asbestos, lead, silica, mold, etc.
- Pneumatic (air-operated)
- Static dissipating and conductive
- Category 2GD (Zone 1 and 21)
- For wet & dry recovery
- Stainless steel Type 430 body and recovery tank
- Ready to use Filters and static dissipative tool kit included
- Equipped with 4 static dissipative wheels. Optional 2+2 cart available
- Low noise level only 68 dB(A)

Website: http://www.tiger-vac.com

Email: sales@tiger-vac.com

Specifications

ATEX-12A (4W)	111962
Model Name	ATEX-12A (4W)
Type (Powerhead)	Pneumatic
Venturi	Single
Minimum Compressor	15 HP
Air Line Size (Diam.)	1/2 "
Input Air Volume	35-45 CFM
Input Air Pressure	80 PSI
Air Flow	110 CFM
Vacuum Pressure	110 " H ₂ 0
Sound Level	68 dB(A)
Suction Inlet Port	2 "
Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	None
Dust Recovery Tank	10 gal.
Liquid Recovery Capacity	12.5 gal.
Length	20.5 "
Width	19 "
Height	32 "
Weight (Vacuum Only)	25.5 lb.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



ATEX/AVSD Tools and Accessories W&D - Included



219841 Pressure Regulator - Optional

Tel: 1-800-668-4437 (954-925-3625) Website: http://www.tiger-vac.com Fax: 1-800-668-4439 (954-925-3626) Email: sales@tiger-vac.com