

Characteristics



Specifications

REGENERATIVE BLOWERS	212746C1*120V	212746C1*230V	212748A*230V	212748A*460V	212748B	212748C*120V
Model Name	REGENERATIVE BLOWER FOR MODELS CD-1501 CR (STD), 2 HP, (RT-3015-1), WIRED FOR 120V, 60 HZ, SINGLE PHASE	REGENERATIVE BLOWER FOR MODELS CD-1501 CR (STD), 2 HP, (RT-3015-1), WIRED FOR 230V, 60 HZ, SINGLE PHASE	REGENERATIVE BLOWER FOR MODELS CD-1501 CR (STD) AND CD-2600 CR SERIES, 2.5 HP, (RT-1900 (RT-4019)), WIRED FOR 230V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-1501 CR (STD) AND CD-2600 CR SERIES, 2.5 HP, (RT-1900 (RT-4019)), WIRED FOR 460V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-1501 CR (STD) AND CD-2600 CR SERIES, 2.5 HP, (RT-1900 (RT-4019)), WIRED FOR 575V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-2600 CR SERIES, 2.5 HP, (RT-1900 (RT-4019)), WIRED FOR 120V, 60 HZ, SINGLE PHASE
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Tension	120 V	230 V	230 V	460 V	575 V	120 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Single	Single	Three	Three	Three	Single
Wattage	1500 W	1500 W	1900 W	1900 W	1900 W	1900 W
Power	2 HP	2 HP	2.5 HP	2.5 HP	2.5 HP	2.5 HP
Amperage	18 A	9 A	7 A	4 A	2.6 A	14 A
Air Flow	120 CFM	120 CFM	148 CFM	148 CFM	148 CFM	140 CFM
Vacuum Pressure	111+ " H ₂ O	111+ " H ₂ O	140 " H ₂ O	140 " H ₂ O	140 " H ₂ O	111+ " H ₂ O
VRV Setting	80 " H ₂ O	80 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O
Sound Level	69 dB(A)	69 dB(A)	dB(A)	dB(A)	dB(A)	dB(A)
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Cord Length	ft.	ft.	50 ft.	50 ft.	50 ft.	50 ft.
REGENERATIVE BLOWERS	212748C*230V	212750A*230V	212750A*460V	212750B	212752A*230V	212752A*460V
Model Name	REGENERATIVE BLOWER FOR MODELS CD-2600 CR SERIES, 2.5 HP, (RT-1900 (RT-4019)), WIRED FOR 230V, 60 HZ, SINGLE PHASE	REGENERATIVE BLOWER FOR MODELS CD-2600 CR SERIES, SRV-55 AND TV-2, 3.5 HP (RT-2200 (RT-5026)), WIRED FOR 230V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-2600 CR SERIES, SRV-55 AND TV-2, 3.5 HP (RT-2200 (RT-5026)), WIRED FOR 460V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-2600 CR SERIES, SRV-55 AND TV-2, 3.5 HP (RT-2200 (RT-5026)), WIRED FOR 575V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-5000, SRV-55, TV-3 AND TV-4, 5 HP (RT-3700 (RT-6037)), WIRED FOR 230V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-5000, SRV-55, TV-3 AND TV-4, 5 HP (RT-3700 (RT-6037)), WIRED FOR 460, 60 HZ, THREE-PHASE
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Tension	230 V	230 V	460 V	575 V	230 V	460 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Single	Three	Three	Three	Three	Three
Wattage	1900 W	2600 W	2600 W	2600 W	3700 W	3700 W
Power	2.5 HP	3.5 HP	3.5 HP	3.5 HP	5 HP	5 HP
Amperage	7.2 A	9.4 A	4.7 A	4 A	13.5 A	7.8 A
Air Flow	140 CFM	219 CFM	219 CFM	219 CFM	220 CFM	220 CFM
Vacuum Pressure	111+ " H ₂ O	145 " H ₂ O	145 " H ₂ O	145 " H ₂ O	155 " H ₂ O	155 " H ₂ O
VRV Setting	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	110 " H ₂ O	120 " H ₂ O	120 " H ₂ O
Sound Level	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)

Tiger-Vac Inc.
11 SW 12th Ave #112
Dania, FL 33004
USA

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: 1-800-668-4437 (954-925-3625)
Fax: 1-800-668-4439 (954-925-3626)

Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com

Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Cord Length	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.	50 ft.
REGENERATIVE BLOWERS	212752B	212756A*230V	212756A*460	212756B	215289C1*120V	215289C1*230V
Model Name	REGENERATIVE BLOWER FOR MODELS CD-5000, SRV-55, TV-3 AND TV-4, 5 HP (RT-3700 (RT-6037)), WIRED FOR 575V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-10000 AND CDPU-10000, 11 HP (RT-7500), WIRED FOR 230V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-10000 AND CDPU-10000, 11 HP (RT-7500), WIRED FOR 460V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-10000 AND CDPU-10000, 11 HP (RT-7500), WIRED FOR 575V, 60 HZ, THREE-PHASE	REGENERATIVE BLOWER FOR MODELS CD-1500 CR (PFB), 850 WATTS, (RT-3009 (RT-0750)), WIRED FOR 120V, 60 HZ, SINGLE PHASE	REGENERATIVE BLOWER FOR MODELS CD-1500 CR (PFB), 850 WATTS, (RT-3009 (RT-0750)), WIRED FOR 230V, 60 HZ, SINGLE PHASE
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
TEFC Motor	Yes	Yes	Yes	Yes	Yes	Yes
Tension	575 V	230 V	460 V	575 V	120 V	230 V
Frequency	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
Phase	Three	Three	Three	Three	Single	Single
Wattage	3700 W	8000 W	8000 W	8000 W	850 W	850 W
Power	5 HP	11 HP	11 HP	11 HP	1.1 HP	1.1 HP
Amperage	5.4 A	23 A	13 A	10.5 A	14 A	7 A
Air Flow	220 CFM	360 CFM	360 CFM	360 CFM	95 CFM	95 CFM
Vacuum Pressure	155 " H ₂ O	145 " H ₂ O	145 " H ₂ O	145 " H ₂ O	110 " H ₂ O	110 " H ₂ O
VRV Setting	120 " H ₂ O	120 " H ₂ O	120 " H ₂ O	120 " H ₂ O	70 " H ₂ O	70 " H ₂ O
Sound Level	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)	dB(A)
Type of Power Outlet	Not Included	Not Included	Not Included	Not Included	Not Included	Not Included
Cord Length	50 ft.	30 ft.	30 ft.	30 ft.	50 ft.	50 ft.

Please note that specifications are subject to change without notice

Use only recommended tools & accessories